



Main

| | |
|----------------|--------------------------|
| Product Range | DPA |
| Component type | Auxiliary Contact Module |
| Used with | contactor |

Complementary

| | |
|-------------------------------|--|
| Auxiliary contact composition | 1 NO |
| Rated breaking capacity | 3 A at 120 V AC for inductive control circuit conforming to UL 508 1.5 A at 240 V AC for inductive control circuit conforming to UL 508 0.75 A at 480 V AC for inductive control circuit conforming to UL 508 0.6 A at 600 V AC for inductive control circuit conforming to UL 508 5 A at <= 600 V AC for resistive control circuit conforming to UL 508 |

Environment

| | |
|------------------------|----------------------|
| Product certifications | CSA UL recognized |
|------------------------|----------------------|

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 1.778 cm |
| Package 1 Width | 4.318 cm |
| Package 1 Length | 7.112 cm |
| Package 1 Weight | 31.752 g |

Offer Sustainability

| | |
|----------------------------|---|
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 Monate |
|----------|-----------|