Dismantling Knives IEC 60900 DIN EN 60900

98 5

- > ergonomically improved handle shape with comfortable slip guard
- > particularly confident grip thanks to slip-proof soft components
- > thumb recess and "finger hook" at the end of the handle ensure a good transmission of force when the blade is pulled
- > transparent protective cap

98 53 03

solid, fixed hook blade; suitable for round cables; blade: special tool steel, oil-hardened

98 53 13

narrow, fixed hook blade, sickle shaped; suitable for sector cables; blade: special tool steel, oil-hardened

98 55

solid, fixed hook blade, sickle shaped; with guide shoe at the blade point; no damage of the conductor insulation; blade: surgical steel, stainless, vacuum-hardened



Guide shoe 98 55







| | EAN | ← ► | | | Blade length | Radius | 47 |
|-------------|----------|------------|--------------------------|---|--------------|--------|----|
| Article No. | 4003773- | mm | | Handle | mm | mm | g |
| 98 53 03 | 026549 | 155 | ≙ 1000 V △ | insulating multi-component handle, VDE-tested | 28 | 7.0 | 77 |
| 98 53 13 | 026556 | 180 | <u>♠</u> 1000 V 🏤🗲 | insulating multi-component handle, VDE-tested | 50 | 40.0 | 77 |
| 98 55 | 022558 | 155 | ☆ 1000 V △ | insulating multi-component handle. VDE-tested | 38 | 23.5 | 77 |

Cable Knife with replaceable blade

98

IEC 60900 DIN EN 60900

- > straight blade with special sharpening; replaceable
- > with hinged blade guard, integrated in the handle, captive
- > back of the blade plastic coated to avoid short circuits
- > ergonomically shaped insulating handle
- > blade: surgical steel, stainless, vacuum-hardened



| Article No. | EAN 4003773- | ←→ mm | | Blade length mm | ∆ d g | | | | |
|--|-----------------|--------------|--------------------------|--------------------|-------------|--|--|--|--|
| 98 56 | 026570 | 185 | ☆ 1000 V △ | 50 | 64 | | | | |
| 98 56 SB | 033516 | 185 | <u>₩</u> 1000 V Ģ | 50 | 64 | | | | |
| 98 56 09 030829 Spare blade for 98 56 | | | | | | | | | |