



Clamp electrodes for textiles



Normed clamp electode accroding to IEC 61340-4-9 for cloths and other texiles.

- Contact area: 25 mm x 50 mm
- Connection: 4 mm safety socket
- P.U.: 2 pcs

Article-No.	Description
EP0204005	Clamp electrode P.U. 2 pcs

Ring electrode set



- For surface and volume resistance measurements
- Cylindrical ring electrode, Ø 70 mm, 170 mm high
- Outer ring diameter 60 mm, inner ring diameter 30 mm
- Weight 2,6 kg, with banana plug adapter
- With conductive carbon-contact rubber (R<500 Ω)
- In set with coax cable and transport case

Article-No.	Description
EP0204003	1 ring electrode in set incl. cable, case

Measuring electrode set



- For leak and point-to-point resistance measurements
- Cylindrical measuring electrode, Ø 63 mm, Weight 2,3 kg
- With conductive carbon-contact rubber (R<500 Ω)
- Delivery incl. 2 electrodes and transport case

Article-No.	Description
EP0204002	Set with 2 electrodes, case
EP0201073	Electrode pair with handle

Miniprobe set



For surface resistance measurements on small packaging, according to IEC 61340-4-10.

- Ideal to measure indentations
- Even pressure through spring-mounted electrode pins
- Conductive contact rubber
- Replaceable measuring head

Contents:

Two-point electode model 844, conductive case, calibration certificate

Article-No.	Description
EP0204004	Miniprobe set
EP0299040	Measuring head with 8 electrodes (spring-mounted pins)
EP0299028	Replacement electrodes (spring-mounted pins), P.U. 2 pcs
EP0299031	Calibration circuit board for Miniprobe