



✓ installation ✓ mobile ✓ RoHS ✓ REACH ✓ CE

Mik-D/D-PVC 2 x 0,22 qmm

double spiral shield

Order-No. 58D202209

Application / Description

For stage, events, studio usage. There is no scope for interferences because the double spiral shielding. The PE core insulation causes to low capacity, the soft PVC jacket is supple and low temperature resistant. For fixed installations, we offer this type also in FRNC/LSZH.



Variant data

O.D.	approx. 6,30 mm
weight	57,0 kg/km
Cu-weight	19,0 kg/km

Construction / audio

Conductor	bare stranded copper wire
Structure of conductor	28 x 0,10 mm mm
Conductor dimension	0,22 qmm
number of cores	2
Core insulation	PE
Overall shield	2 x bare copper spiral screen, moving in opposite directions
Outer jacket	Soft-PVC
Outer jacket colour	black
Dimension	2 x 0,22 qmm

Technical characteristics

Temperature range	static: -30 °C to +70 °C dynamic: -15 °C to +70 °C
Bending radius	> 10 x O.D.
Operating capacity (C/C)	approx. 58 pF/m
Operating voltage	500 V

Testing voltage	1.200 V
-----------------	---------

Packaging

Rings, Spools, Reels

Lower and upper lengths according to availability. Special packaging on request.

© kabeltronik® Arthur Volland GmbH

Mühlweg 6, 85095 Denkendorf

Tel.: 08466 - 9404-0

E-Mail: info@kabeltronik.de

