

AMPLIMITE | AMPLIMITE HD-20

TE Internal #: 5745968-2

AMPLIMITE HD-20, PCB D-Sub Connectors, Plug, Board-to-Board,

25 Position, 2.74mm [.108in] Centerline, 2 Row, Row-to-Row

Spacing 2.84 mm [.112 in]

View on TE.com >



Connectors > D-Shaped Connectors > D-Sub Connectors > PCB D-Sub Connectors











Connector & Housing Type: Plug

Connector System: Board-to-Board

Number of Positions: 25

Centerline (Pitch): 2.74 mm [.108 in]

Number of Rows: 2

Features

Product Type Features

Grounding Indents	With
Grounded	Yes
Grounding Straps	Without
Shell Type	Front Metal Shell
Connector & Housing Type	Plug
Connector System	Board-to-Board
D-Sub Shell Size	3
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Shielded	Yes
Product Type	Connector
Configuration Features	
Number of Positions	25
Number of Rows	2



PCB Mount Orientation	Vertical
Preloaded	Yes
Body Features	
Plastic	No
Insert Material	Brass
Connector Profile	Standard
Shell Plating Material	Tin
Shield Material	Steel
Shell Material	Carbon Steel
Post Size	.66 mm[.026 in]
Shield Plating Material	Tin
Contact Features	
Contact Mating Area Plating Material	Gold
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Brass
Contact Shape & Form	Round
Contact Current Rating (Max)	6 A
	30 μin
Termination Features	
Grounding Clips	Without
Termination Method to Printed Circuit Board	Through Hole - Solder
Termination Post Length	3.18 mm[.125 in]
Mechanical Attachment	
Panel Mount Feature	Without
PCB Mount Retention	With
PCB Mount Retention Type	Mounting Hole
Mating Retention	Without
Connector Mounting Type	Board Mount
Mounting Hole Diameter	3.05 mm[.12 in]
Housing Features	
Centerline (Pitch)	2.74 mm[.108 in]



Housing Material	Polyester
Housing Color	Black
Dimensions	
Row-to-Row Spacing	2.84 mm[.112 in]
PCB Thickness (Recommended)	1.57 – 2.36 mm[.062 – .093 in]
Usage Conditions	
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Operation/Application	
Circuit Application	Signal
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Method	Tube
Packaging Quantity	10
Other	
Comment	Plugs are preloaded with size 20 DF posted pin contacts

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2020 (205) Candidate List Declared Against: JAN 2020 (205) Does not contain REACH SVHC
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2020 (205) Candidate List Declared Against: JAN 2020 (205)
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts



TE Model / Part # 1-745495-8 25 HDE MS RCPT,22-26,LEAD FREE



TE Model / Part # 1-745495-7 25 HDE MS RCPT,26-30,LEAD FREE




TE Model / Part # 5746861-2 25 POS HDF RCPT, MS













Also in the Series | AMPLIMITE HD-20





Customers Also Bought



TE Model / Part #745968-2 25 PLUG SP/FMS STD



TE Model / Part #5747872-4 15 PLUG SP/FMS STD



TE Model / Part #1761606-6
IDC LOW PRO HDR 16P VERT LG LAT
BLK





TE Model / Part #5745967-2 25 RCPT SP/FMS STD



TE Model / Part #1-770966-1 02P MINI UMNL R/A HDR ASSY AU



TE Model / Part #5-146285-3 03 MODII HDR SRST B/A .100CL







TE Model / Part #5-146281-3 03 MODII HDR SRST B/A LF



Documents

Product Drawings
25 PLUG SP/FMS STD

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_5745968-2_C.2d_dxf.zip



English

Customer View Model

ENG_CVM_CVM_5745968-2_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_5745968-2_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

AMPLIMITE Subminiature D Connectors - Straight Posted Connectors

English

Product Specifications

Application Specification

English

Product Environmental Compliance

MD_5745968-2_04052018525_dmtec

English

MD_5745968-2_04052018525_dmtec

English

Agency Approvals

UL Report

English