EVP1CBS321C45

EVlink, Attached cable T2 32A 1-Ph IEC 4,5m Smart Wallbox



Main	
Range	EVlink
Product or component type	Charging cable
Accessory / separate part category	Spare part
Network number of phases	Single phase
Poles description	1P + N
[In] rated current	32 A
[Us] rated supply voltage	220240 V AC 50/60 Hz
Earthing system	Compatible TN Compatible IT with additional isolation transformer on the power supply Compatible TT
Nominal output power	7.4 W 32 A
Socket number	1

Complementary

Connector type	T2 vehicle end silver plated contacts Without connector charging station end	
Range compatibility	EVlink (EVlink Smart Wallbox) EVB1 charging station	
Standards	IEC 62196-2 IEC 62196-1	
Product certifications	CE	
Length	4.5 m	-
Net weight	2.6 kg	

Environment

IP degree of protection	IP54 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262
Ambient air temperature for operation	-3050 °C
Ambient air temperature for storage	-4080 °C
Relative humidity	595 %

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	15.0 cm	
Package 1 Width	30.0 cm	
Package 1 Length	40.0 cm	
Package 1 Weight	1.872 kg	
Unit Type of Package 2	S02	
Number of Units in Package 2	1	
Package 2 Height	15 cm	
Package 2 Width	30 cm	
Package 2 Length	40 cm	
Package 2 Weight	2.308 kg	
Package 3 Height	80 cm	

Offer Sustainability

REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EPEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	☑ China RoHS Declaration	
RoHS exemption information	₫Yes	

Contractual warranty

Warranty	18 Monate
----------	-----------