



Bendable Universal Plug

Bendable up to 180°, with screw terminals, with or without strain relief, adaptor that can be firmly positioned by a bayonet catch, 12-24 V, fitting for cigarette lighter and standard sockets.

	ВР	SP
	SU = 100	SU = 60
8 A with screwed strain relief	67741000	67741500
8 A without strain relief	67741100	_

Bendable Safety Universal Plug

Bendable up to 180° , with screw terminals, with or without strain relief, adaptor that can be firmly positioned by a bayonet catch, $12\text{-}24\,\text{V}$, fitting for cigarette lighter and standard sockets. With integrated, interchangeable fuse from $1\text{-}8\,\text{A}$ / $12\text{-}24\,\text{V}$.

	ВР	SP
fused	SU = 100	SU = 60
1 A with screwed strain relief	67742001	_
2 A with screwed strain relief	67742002	-
8 A with screwed strain relief	67742000	67742500
1 A without strain relief	67742101	-
2 A without strain relief	67742102	-
8 A without strain relief	67742100	_



Example of use

Offering sufficient space for your electronics.

dimensions for pcb:

- with screwed strain relief = 28.5 x 26.5 x 1.5 mm
- strain relief by prommet = $35.5 \times 26.5 \times 1.5 \text{ mm}$



Bendable Universal Plug with switch

 $8\,\text{A}$ / $12\text{-}24\,\text{V}$, with single-pole circuit breaker $8\,\text{A}$, rocker switch imprinted with 0-I. The plug is bendable up to 180° , with screw terminals, adaptor that can be firmly positioned by a bayonet catch, fitting for cigarette lighter and standard sockets.

	BP	SP
	SU = 100	SU = 60
8 A	67746000	67746500

Bendable Safety Universal Plug with switch

 $8\,A$ / 12- $24\,V$, with single-pole circuit breaker $8\,A$, rocker switch imprinted with 0-1. The plug is bendable up to 180° , with screw terminals, adaptor that can be firmly positioned by a bayonet catch. With integrated, interchangeable fuse $8\,A$, fitting for cigarette lighter and standard sockets.

	ВР	SP
fused	SU = 100	SU = 60
8 A	67747000	67747500



Bendable Universal Plug with switch

 $8\,A$ / $12\text{-}24\,V$, with single-pole circuit breaker $8\,A$, rocker switch imprinted with 0-I, assembled with cable $2\times0.75~\text{mm}^2$, length 2.0~m. The plug is bendable up to 180° , with screw terminals, adaptor that can be firmly positioned by a bayonet catch, fitting for cigarette lighter and standard sockets.

	ВР	SP
	SU = 100	SU = 60
8 Δ	67745000	677/5500

Bendable Safety Universal Plug with switch

 $8\,\text{A}$ / $12\text{-}24\,\text{V}$, with single-pole circuit breaker $8\,\text{A}$, rocker switch imprinted with 0-I, assembled with cable $2\times0.75~\text{mm}^2$, length 2.0~m. The plug is bendable up to 180° , with screw terminals, adaptor that can be firmly positioned by a bayonet catch. With integrated, interchangeable fuse $8\,\text{A}$, fitting for cigarette lighter and standard sockets.

	ВР	SP
fused	SU = 100	SU = 60
8 A	67748000	67748500