Crimping Dies

for KNIPEX Crimp System Pliers Art. No.: 97 43 XX

> Up to 250 different die profiles available; special profiles on request

Article No.	EAN 4003773-			Applications	Capacity mm²	AWG	Capacity SW mm	Sleeves Ø mm
97 49 04	030850	fo.	M	non-insulated open plug type connectors (plug width 2.8 + 4.8 mm)	0.1 - 2.5	27 - 13		
97 49 05	030867		M	non-insulated open plug type connectors (plug width 4.8 + 6.3 mm)	0.5 - 6	20 - 10		
97 49 06	030836	1	5	insulated terminals, plug connectors + butt connectors	0.5 - 6	20 - 10		
97 49 07	077749		•	heat shrinkeable sleeve connectors	0.5 - 6	20 - 10		
97 49 08	030874		'	insulated and non-insulated wire ferrules	0.25 - 6	23 - 10		
97 49 09	030881		$ldsymbol{ld}}}}}}}$	insulated and non-insulated wire ferrules	10 / 16 / 25	7/5/3		
97 49 10	076896		V	non-insulated tubular cable lugs and crimp terminals in accordance with DIN 46237 and non-insulated butt and crimp connectors in accordance with DIN 46341	0.25 - 0.75 / 1 - 1.5 / 2.5	13 / 15 - 17 / 19 - 20		
97 49 11	076902	25	~	non-insulated crimp terminals, tube and compression cable lugs in accordance with DIN 46234 and DIN 46235 and non-insulated crimp, butt and press connectors in accordance with DIN 46341 and DIN 46267	4/6/10	11 / 10 / 7		
97 49 14	077756		~	for non-insulated crimp terminals, tube and compression cable lugs in accordance with DIN 46234 and DIN 46235 and non-insulated crimp, butt and press connectors in accordance with DIN 46341 and DIN 46267	0.5 - 10	20 - 7		
97 49 15	043164	Service Services	M	for plug connectors and angled spade connectors according to DIN 46346 Form A (1.5 - 2.5 mm²)/ for non-insulated, open lug connectors (straight version) according to DIN 46247 (2.5 – 6 mm²)	1.25 - 2.5 / 3 - 6			
97 49 16	040675		^	insulated terminals + cable connectors	10 - 16	7 / 5		
97 49 18	063186		W	Twin wire ferrules for two flexible conductors	6 / 10 / 16			
97 49 19	030898		¥	insulated and non-insulated wire ferrules	35 - 50	2/0		
97 49 20	045069	(100)		F-connectors for TV and satellite connections			7.0 / 8.4 / 8.1	7.7 / 9.5 / 9.5
97 49 23	052135	d	V	non-insulated terminals + cable connectors	16 / 25	5/3		
97 49 24	030911		_^_	D Sub; HD 20; HDE plug	0.03 - 0.56	32 - 20		
97 49 25	079798		_^_	for crimping connectors from the Micro-Fit™ series from Molex LLC		30 - 26 / 24 - 22 / 20		
97 49 26	079804		_^_	for crimping connectors in the Mini-Fit® series from Molex LLC		24 - 20 / 18 / 16		
97 49 27	079811		_^_	MQS connectors	0.25 / 0.35 / 0.5	24 / 22 / 20		
97 49 28	083757	- Company	M	connectors of the AMP Superseal 1.5 series from Tyco Electronics	0.35 - 0.5 / 0.75 / 1 / 1.5	32 - 20		
97 49 30	030904	Contract of the Contract of th		non-insulated crimp connectors in accordance with DIN 46267	1.5 - 4 6 / 10	15 - 7 10 / 7		
97 49 35	034315	<u></u> ()	M	spark plug connectors and distributors	1	17		
97 49 40	030959	650 °	•	Coax connectors RG 58, 59, 62, 71, 223			5.4 / 6.48 / 1.72	6.4 / 7.6 / 2.1