



Main

Range of product	Lexium 32i
Product or component type	Control unit
Device short name	LXM32i
Format of the drive	Board
Discrete input number	2 safety discrete input(s) 4 logic discrete input(s)
Discrete input type	Safety (compliment of STO_A, compliment of STO_B terminals) Logic (DI terminals)

Complementary

Sampling duration	DI: 0.25 ms discrete
Discrete input voltage	24 V DC for capture 24 V DC for logic 24 V DC for safety
Discrete input logic	Positive (compliment of STO_A, compliment of STO_B) at State 0: < 5 V at State 1: > 15 V conforming to EN/IEC 61131-2 type 1 Positive (DI) at State 0: > 19 V at State 1: < 9 V conforming to EN/IEC 61131-2 type 1 Positive or negative (DI) at State 0: < 5 V at State 1: > 15 V conforming to EN/IEC 61131-2 type 1
Response time	<= 5 ms compliment of STO_A, compliment of STO_B
Discrete output number	2
Discrete output type	Logic output(s) (DO) 24 V DC
Discrete output voltage	<= 30 V DC
Discrete output logic	Positive or negative (DO) conforming to EN/IEC 61131-2
Contact bounce time	<= 1 ms for compliment of STO_A, compliment of STO_B 0.25 µs...1.5 ms for DI
Braking current	50 mA
Response time on output	250 µs (DO) for discrete output(s)
Control signal type	Servo motor encoder feedback
Protection type	Against reverse polarity: inputs signal Against short-circuits: outputs signal
Safety function	Safe torque off safety function, integrated
Safety level	SIL 3 conforming to EN/IEC 61508 PL = e conforming to ISO 13849-1
Communication interface	Profinet, integrated
Connector type	RJ45 for Modbus M12 for PROFINET
Method of access	Slave
Physical interface	2-wire RS485 multidrop for Modbus
Transmission rate	9600, 19200, 38400 bps for bus length of 0...40 m for Modbus
Number of addresses	1...127 for CANopen, CANmotion 1...247 for Modbus
Status LED	1 LED (red) servo drive voltage 1 LED error 1 LED RUN

Electromagnetic compatibility	Conducted EMC conforming to EN 55011 class A group 1 Conducted EMC conforming to EN 55011 class A group 2 Conducted EMC conforming to EN/IEC 61800-3 environment 2 category C3 Conducted EMC conforming to IEC/EN 61800-3 category C2 EMC immunity conforming to IEC/EN 61800-3 environments 1 and 2 EMC immunity level 3 conforming to EN/IEC 61000-4-2 EMC immunity level 3 conforming to EN/IEC 61000-4-3 EMC immunity level 3 conforming to EN/IEC 61000-4-5 EMC immunity level 4 conforming to EN/IEC 61000-4-4 Radiated EMC conforming to EN 55011 class A group 2 Radiated EMC conforming to IEC/EN 61800-3 category C3
Type of cooling	Natural convection
Operating altitude	≤ 1000 m without derating > 1000...3000 m with conditions
Operating position	Vertical +/- 10 degree
Net weight	0.63 kg







Environment

Standards	EN/IEC 61800-3 EN/IEC 61800-5-1
Product certifications	TÜV UL CSA
Marking	CE
IP degree of protection	IP65
Vibration resistance	1 gn (f= 13...150 Hz) conforming to EN/IEC 60068-2-6 1.5 mm peak to peak (f= 3...13 Hz) conforming to EN/IEC 60068-2-6
Shock resistance	15 gn for 11 ms conforming to EN/IEC 60028-2-27
Pollution degree	2 conforming to EN/IEC 61800-5-1
Environmental characteristic	Classes 3C1 conforming to IEC 60721-3-3
Relative humidity	Class 3K3 (5 to 85 %) without condensation conforming to IEC 60721-3-3
Ambient air temperature for operation	0...50 °C conforming to UL
Ambient air temperature for storage	-25...70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.3 cm
Package 1 Width	16.7 cm
Package 1 Length	23.5 cm
Package 1 Weight	630 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
PVC free	Yes

Contractual warranty

Warranty	18 Monate
----------	-----------