



## **Pan-Ty® PLT3I-C0 Cable Tie, Black, UV PA6.6, 11.4"L, 40lb, PK100**

### **PLT3I-C0**

Panduit PLT3I-C0 Locking Cable Ties are designed to satisfy the needs of weather resistant applications, while delivering consistent performance and reliability. Featuring a curved tip to allow for easy pick up from flat surfaces and faster initial threading. Intermediate cross section, 11.4" (290mm) length. Made of Weather Resistant Nylon 6.6, are black in color and come in packages of 100.

### **Specifications**

Product Type	Premium Cable Tie
Color	Black
Environment	Indoor/Outdoor
Material	Weather Resistant Nylon 6.6
Resistance Properties	UV Resistant
Overall Length (In.)	11.4
Overall Length (mm)	290
Body Width (In.)	0.145
Body Width (mm)	3.7
Body Thickness (In.)	0.052
Body Thickness (mm)	1.3
Maximum Bundle Diameter (In.)	3
Maximum Bundle Diameter (mm)	76
Minimum Bundle Diameter (In.)	0.06
Minimum Bundle Diameter (mm)	1.5
Minimum Loop Tensile Strength (N)	178
Minimum Loop Tensile Strength (lb)	40
Maximum Operating Temperature (°C)	85
Maximum Operating Temperature (°F)	185
Minimum Operating Temperature (°C)	-60
Minimum Operating Temperature (°F)	-76
Minimum Installation Temperature (°C)	-20
Minimum Installation Temperature (°F)	-4
Standards Met	CSA Certified, UL Recognized (File #E56854), UL 62275 Compliant (Type 2, 21), RoHS Compliant
For Use With	GTS-E, GS2B-E, PTS, PPTS, STS2

**Specifications (continued)**

Part Features	One-piece locking wedge for consistent performance and reliability. Low thread force and high loop tensile strength.
---------------	--

**Packaging Detail**

UPC	07498354055
Std. Pkg. Qty.	100
Std. Pkg. Volume (cf)	0.0502
Std. Ctn. Qty.	1000
Std. Ctn. Volume (cf)	0.5019