

ScopeMeter® Portable Oscilloscopes Accessories

FLUKE®



TRM50



VPS410-II-X



VPS420-X



VPS510-X



STL120-III



VPS40-III

ScopeMeter Series	190 Series-II			120 Series	
Type of Accessory	VPS410-II-X	VPS420-X	VPS510-X	STL120-III	VPS40-III
Description	Voltage Probe	Voltage Probe	Voltage Probe	Shielded Test Leads	Voltage Probe
Colors available	Red, Grey, Blue, Green	Red-Black, Grey-Black, Blue-Black, Green-Black	Red, Grey, Blue, Green	Red, Grey	Black
Attenuation	10:1	100:1	10:1	1:1	10:1
Bandwidth	500MHz	150MHz	500MHz	12.5MHz	40MHz
Length	1.2m	1.2m	1.2m	1.2m	1.2m
Safety Rating CAT II	--	--	--	1000V	1000V
Safety Rating CAT III	1000V	1000V*	300V	600V	600V
Safety Rating CAT IV	600V	600V*	--	--	--

*High working Voltage Probe is specified for working voltages (between probe tip an reference lead) up to 2000V in CATII or 1200V in CAT IV environment.
Reference lead voltage (between reference lead and earth ground): 1000V in CATIII, 600V in CATIV. These specifications apply only when used with Fluke 190 Series-II Test Tool.



VPS420



PM9091 / PM9092



PM9081



PM9082



PM9093

	PM9091	PM9092	PM9081	PM9082	PM9093
Description	Safety designed 500, BNC cable Set (1 Red, 1 Black, 1 Grey)		Dual banana plug male to female BNC	Dual banana jack female to male BNC	Male BNC to dual female BNC (T-piece)
Length	1.5 m each	0.5 m each	--	--	--
Safety Rating CAT III	600 V	600 V	600 V	600 V	600 V



RS400



AS400



BP290



BP291



OC4USB



EBC290

Optional accessories Fluke 190 Series-II

AS400	Probe Accessory Extension Set for VPS400 Series Voltage Probes
BC190	Line Voltage Adapter and Battery charger
BC190/820	SMPS Power Adapter and Battery charger
BP290	Single Capacity, Rechargeable Li-Ion Battery Pack, 2400 mAh
BP291	Double Capacity, Rechargeable Li-Ion Battery Pack, 4800 mAh
C195	Protective Carrying Case
C290	Hard Shell Protective Carrying Case
C437-II	Hard Shell, Protective Carrying Case with rollers
EBC290	External Battery Charger
HC200	Hook Clip Replacement Set
HH290	Hanging Hook
MA190	Medical Applications Accessory Kit
RS400	Probe Accessory Replacement Set for VPS400 Series Voltage Probes
RS500	Probe Accessory Replacement Set for VPS510 Series Voltage Probes
SCC290	Software and Carrying Case Kit
SCC298	Automotive Troubleshooting Kit for Fluke Series-II
SKMD-001	Motors & Drive Tool Kit
SW90W	FlukeView® ScopeMeter® software for Windows®
TL175	TwistGuard™ Test Lead Set
TRM50	Coaxial Feed-through BNC male to BNC female Cable terminator, 50 ohm
VPS101	Double isolated Voltage probe Set, 1:1, 30MHz, Black
VPS220-X	Voltage Probe Set, 100:1, 200MHz. X= Red or Grey color
VPS410-II-X	Industrial type Voltage Probe, 10:1, 500MHz. X= B(Blue) or G(Grey) or R(Red) or V(Green) color
VPS420-X	High Working Voltage Probe 100:1, 150MHz. X= B(Blue-Black) or G(Grey-Black) or R(Red-Black) or V(Green-Black) Bicolor
VPS510-X	Compact, Wide Bandwidth probe for electronic applications, 10:1, 500MHz, X= B(Blue) or G(Grey) or R(Red) or V(Green) color