

RAFIX 16, lamp socket W2 x 4.6d, quick-connect terminal, for W 2 x 4.6d



fields of application

- Measurement-control-regulation
- Electrical engineering
- Mechanical and system engineering
- Industrial robots

special features

- Lampenfassung Wedge-Base W 2x4.6d für LED
- Eine Kerbe an der Lampenfassung kennzeichnet die Kathodenseite.
- Montage durch Aufrasten oder Einrasten in Meldeleuchte
- Flachsteck-Anschlüsse 2,8 x 0,8 mm

description

Lampenfassung zum Ein- oder Aufrasten auf Meldeleuchten.

technical data

➤ general

illuminated	Yes
Color	light gray
Operating temperature, min.	-25 °C
Operating temperature, max.	55 °C
Storage temperature, min.	-40 °C
Storage temperature, max.	85 °C
Lamp socket	W 2 x 4.6d
Vibration-resistance according to standard IEC 60068-2-6	10 g at 20 - 500 Hz
Shock resistance according to standard IEC 60068-2-27	50 g at 11 ms amplitude semi-sinusoidal
Packaging unit	5 pcs.
net weight	7.4 g
standard delivery time	3 weeks
Environment resistance	IEC 60068-2-14 IEC 60068-2-30 IEC 60068-2-33 IEC 60068-2-78
RoHS compliant	Yes
REACH compliant	Yes

direct links

- [RAFI eCatalog](#)

MOQ order	5
> mounting diameters	
Mounting depth	44.7 mm
Outside dimension, length	22.2 mm
Outside dimension, width	22.2 mm
Outside dimension, height	34.4 mm
> mechanical data	
Fixing	Latching
Terminal on the rear	Flat quick-connect terminal 2.8 x 0.8
Lötbarkeit	No

drawings

System drawing

