



Main

Range	EVlink
Product or component type	Socket-outlet
Socket-outlet type	T2
Poles description	3P + N
[Us] rated supply voltage	380...415 V AC 50/60 Hz
Maximum supply current	32 A
Earthing system	Compatible TT Compatible IT with additional isolation transformer on the power supply Compatible TN
Nominal output power	22 W 32 A
Range compatibility	EVlink (EVlink Wallbox) EVH2 charging station

Complementary

Material	Plastic
Product certifications	CE
Height	110 mm
Width	110 mm
Depth	90 mm

Environment

IP degree of protection	IP54 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262
Ambient air temperature for operation	-30...50 °C
Ambient air temperature for storage	-40...80 °C
Relative humidity	5...95 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15 cm
Package 1 Width	15 cm
Package 1 Length	30 cm
Package 1 Weight	637 g
Unit Type of Package 2	S01
Number of Units in Package 2	1
Package 2 Height	15 cm
Package 2 Width	15 cm
Package 2 Length	40 cm
Package 2 Weight	862 g

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

Contractual warranty

Warranty	18 Monate
----------	-----------