



Main

Range of product	Multi9
Product or component type	Shunt trip release
Device short name	MX
[Uc] control circuit voltage	12...24 V AC 50/60 Hz 12...24 V DC
9 mm pitches	2

Complementary

Range compatibility	Multi 9 (Multi9 C60) C60BP Multi 9 (Multi9 C60) C60BPR Multi 9 (Multi9 C60) C60SP Multi 9 (Multi9 GFP) GFP Multi 9 (Multi9 C60H-DC) C60H-DC
Local signalling	Action indicator
Mounting mode	Fixed
Mounting support	DIN rail
Comb busbar and distribution block compatibility	Top: YES
Height	82.5 mm
Width	18 mm
Depth	68 mm
Net weight	0.06 kg
Connections - terminals	Clamp terminal (bottom) - 1 cable(s) 2.5 mm ² (AWG 14) - rigid Clamp terminal (bottom) - 2 cable(s) 1.5 mm ² (AWG 16) - rigid
Wire stripping length	9 mm for bottom connection
Tightening torque	1 N.m bottom

Environment

Standards	EN/IEC 60947-1
Product certifications	UR PCT CSA UL
Pollution degree	3
Tropicalisation	2 conforming to EN/IEC 60947-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.000 cm
Package 1 Width	7.800 cm
Package 1 Length	9.400 cm

Package 1 Weight	70.900 g
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	9.000 cm
Package 2 Width	10.000 cm
Package 2 Length	26.500 cm
Package 2 Weight	634.000 g
Unit Type of Package 3	S03
Number of Units in Package 3	72
Package 3 Height	30.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	6.218 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile

Contractual warranty

Warranty	18 Monate
----------	-----------