## KNIPEX Cobra® VDE

## **Hightech Water Pump Pliers, insulated**

- > Adjustment by shifting one jaw directly on to the workpiece: fast, reliable and comfortable handling
- > Fine adjustment: allows optimum adjustment to differently sized workpieces and comfortable handle position
- > Good access to the workpiece due to slim size of head and joint area
- > Self-locking on pipes and nuts: no slipping on the workpiece and low handforce required
- > Gripping surfaces with special hardened teeth, teeth hardness approx. 61 HRC: high wear resistance and stable gripping
- > Box-joint design for high stability due to double guide
- > Pinch guard prevents operators' fingers being pinched
- > Chrome vanadium electric steel, forged, multi stage oil-hardened
- > DIN ISO 8976, DIN EN 60900, IEC 60900



> Pliers with tether attachment point for mounting a fall protection



The adjustment action to adapt to the workpiece is easy and reliable with the KNIPEX Cobra® VDE: place the upper gripping jaw of the opened pliers on the workpiece, push pliers to close, done!

Article No.	EAN 4003773-	<b>←→</b> mm		Pliers	Head	Handles	O∄ Ø Inch	O] Ø mm	mm	Adjustment positions	ΔΔ g
87 26 250	071495	250	1000 V △ €	chrome plated	chrome plated	insulated with multi-component grips, VDE-tested	2	50	46	24	340
87 26 250 T	081517	250	∰ <u>A</u> 1000 V	chrome plated	chrome plated	insulated with multi-component grips, VDE-tested with integrated insulated tether attachment point for a tool tether	2	50	46	24	400
87 29 01	079002	range of spare parts for 87 2x-250									

## KNIPEX Cobra® ES

## Water Pump Pliers extra-slim


- > Ideal for service, maintenance and equipment repair, in automotive and general industry
- > Long, narrow jaws
- > Particularly good access to the workpiece due to very slim construction of head and joint area
- > Firm grip also on flat material due to three-point rest
- > Push the button for adjustment on the workpiece
- > Fine adjustment for optimum adaptation to different sizes of workpieces and a comfortable handle width
- > Self-locking on pipes and nuts: no slipping on the workpiece and low handforce required
- > Box-joint design for high stability due to double guide
- > Reliable catching of the hinge bolt: no unintentional shifting
- > Favourable lever action: optimum transmission of force
- > Pinch guard prevents operators' fingers being pinched
- > Chrome vanadium electric steel, forged, multi stage oil-hardened
- > DIN ISO 8976

87 51 250





Optimum access to the workpiece. Ideal for service, maintenance and equipment repair, in automotive and general industry





Very slim design in the complete head and joint area (compared to conventional water pump pliers)

10	Coloris 37 51 250 was incumen
(F)	
	talkalklemmend ( and tucking

	EAN	<b>←</b> ►				O]	CO	$\bigcirc$	max. parallel	max. gripping	Adjustment	7,7
Article No.	4003773-	mm	Pliers	Head	Handles	Ø Inch	Ømm	mm	opening width	depth	positions	g
87 51 250	061267	250	grev atramentized	polished	with non-slip plastic coating	1 1/4	32	34	37	42	19	328