



✓ installation ✓ mobile ✓ outdoor ✓ RoHS ✓ REACH ✓ CE

Sensocord®-M 3 x 0,09 qmm

Miniature-Sensor cable

Order-No. 246300909

Application / Description

Drag chainable miniature-sensor cable with PUR-jacket. Mechanical durability and a very good stability against oils as well as UV-radiation, will distinguish this line for the industrial sector as well as for outdoor using.



Variant data

O.D.	approx. 2,40 mm
weight	8,0 kg/km
Cu-weight	2,9 kg/km
skinning tool (jacket)	40025
skinning tool (core)	20100

Construction / data

Conductor	finest bare copper wire, acc. to DIN VDE 0295
Structure of conductor	19 x 0,079 mm
Conductor dimension	0,09 qmm
Core-Ø	approx. 0,65 mm
AWG	28
number of cores	3
Core insulation	PP
Core colour sequence	brown, blue, black
Twisting	cores in layers
Outer jacket	composite jacket: inside PVC, outside PUR
Outer jacket colour	black, sim. RAL 9005
Dimension	3 x 0,09 qmm

Technical characteristics

Temperature range	static: -30 °C to +80 °C dynamic: -15 °C to +80 °C
-------------------	---

Bending radius static	> 8 x O.D.
Bending radius dynamic	> 12 x O.D.
Bending radius e-chain	> 15 x O.D.
Operating voltage	300 V
Testing voltage	1.200 V
Insulation resistance	> 200 MOHM x km at + 20°C

Packaging

Spools at 100m

Lower and upper lengths according to availability. Special packaging on request.

Add-on information

Small Outside Diameter, very good industrial working because PVC/PUR jacket, application also in the automotive section.

© kabeltronik® Arthur Volland GmbH

Mühlweg 6, 85095 Denkendorf

Tel.: 08466 - 9404-0

E-Mail: info@kabeltronik.de

