



## Pan-Ty® PLT4H-L0 Cable Tie, Black, UV PA6.6, 14.5"L, 120lb, PK50

PLT4H-L0

Panduit PLT4H-L0 Locking Cable Ties are designed to satisfy the needs of general applications, while delivering consistent performance and reliability. Featuring a curved tip to allow for easy pick up from flat surfaces and faster initial threading. Light-heavy cross section, 14.5" (368mm) length. For Indoor/Outdoor use, made of Weather Resistant Nylon 6.6, are black in color and come in packages of 50.

### Specifications

Product Type	Premium Cable Tie
Color	Black
Environment	Indoor/Outdoor
Material	Weather Resistant Nylon 6.6
Resistance Properties	UV Resistant
Overall Length (In.)	14.5
Overall Length (mm)	368
Body Width (In.)	0.3
Body Width (mm)	7.6
Body Thickness (In.)	0.075
Body Thickness (mm)	1.9
Maximum Bundle Diameter (In.)	4
Maximum Bundle Diameter (mm)	102
Minimum Bundle Diameter (In.)	0.188
Minimum Bundle Diameter (mm)	4.8
Minimum Loop Tensile Strength (N)	534
Minimum Loop Tensile Strength (lb)	120
Maximum Operating Temperature (°C)	85
Maximum Operating Temperature (°F)	185
Minimum Operating Temperature (°C)	-60
Minimum Operating Temperature (°F)	-76
Minimum Installation Temperature (°C)	-20
Minimum Installation Temperature (°F)	-4
Standards Met	CSA Certified, UL Recognized (File #E56854), UL 62275 Compliant (Type 2, 21), RoHS Compliant
For Use With	GTH-E, GS4H-E, GS4EH-E, PTH, STH2, ST3EH

**Specifications (continued)**

Part Features	One piece construction provides consistent, reliable performance. Low thread force.
---------------	--

**Packaging Detail**

UPC	07498354092
Std. Pkg. Qty.	50
Std. Pkg. Volume (cf)	0.0534
Std. Ctn. Qty.	500
Std. Ctn. Volume (cf)	0.5339