

EVP1PSS2

EVlink PKG T2 SOCKET GREEN

TRANSPARENT EV SPARE PART



Main

Range	EVlink
Product or component type	Socket-outlet
Socket-outlet type	T2
Poles description	3P + N
[Us] rated supply voltage	380...415 V AC 50/60 Hz
Maximum supply current	32 A
Range compatibility	EVlink (EVlink parking) EVF2 charging station EVlink (EVlink parking) EVW2 charging station EVlink (EVlink parking) EVP2 enclosure

Complementary

Material	Plastic
Height	260 mm
Width	110 mm
Depth	80 mm
Net weight	1.34 kg
Colour	Green





Environment

IP degree of protection	IP54 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262
Ambient air temperature for operation	-30...50 °C
Ambient air temperature for storage	-40...80 °C
Relative humidity	5...95 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.0 cm
Package 1 Width	14.0 cm
Package 1 Length	28.0 cm
Package 1 Weight	1.583 kg
Unit Type of Package 2	S03
Number of Units in Package 2	2
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	3.58 kg

Offer Sustainability

REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes

Contractual warranty

Warranty	18 Monate
----------	-----------