NSYS3D5425

Spacial S3D plain door w/o mount.plate. H500xW400xD250 IP66 IK10 RAL7035.





Main

Complementary

Single piece body	
Front face: 1 door(s)	
Reversible (120 °)	
3 mm double-bar lock	
Front	
Door by hinges	
Cable gland plate by screws	
Steel	
Epoxy-polyester powder	
Grey (RAL 7035)	
IEC 62208	
DNV	
UL	
BV	
LR	
CUL	
GL	
10.2 kg	
	Reversible (120 °) 3 mm double-bar lock Front Door by hinges Cable gland plate by screws Steel Epoxy-polyester powder Grey (RAL 7035) IEC 62208 DNV UL BV LR CUL GL

Environment

NEMA degree of protection	NEMA 4X/13
IK degree of protection	IK10 conforming to IEC 62262
IP degree of protection	IP66 conforming to IEC 60529

Packing Units

0	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	29 cm
Package 1 Width	42 cm
Package 1 Length	51 cm
Package 1 Weight	9.14 kg
Unit Type of Package 2	PAM
Number of Units in Package 2	27
Package 2 Height	170 cm
Package 2 Width	100 cm
Package 2 Length	120 cm
Package 2 Weight	269 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) [™] EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	☐ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months