

Housing - HC-HPR-B10-HHWH-1TTM32-EM-BK



1411067

<https://www.phoenixcontact.com/gb/products/1411067>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



HEAVYCON B10 sleeve housing, HPR series, with screw locking, with M32 thread, straight outlet, for increased environmental and EMC requirements

Your advantages

- Vibration and shock: IEC 61373/EN 50155, category 1, class 1B

1411067

<https://www.phoenixcontact.com/gb/products/1411067>

Commercial Data

Item number	1411067
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	BF7AAI
Product Key	BF7AAI
Catalog Page	Page 627 (C-4-2015)
GTIN	4046356921503
Weight per Piece (including packing)	540 g
Weight per Piece (excluding packing)	540 g
Customs tariff number	85389099
Country of origin	CN

Technical Data

Notes

General	For contact inserts HC-B10, BB18, DD42, M, K8/24
---------	--

Product properties

Type	B10
Product type	Housing with screw locking
Application	Railway applications
No. of cable outlets	1
Type of the screw connection	1x M32
Housing type	Sleeve housing
Protective cover	no
Locking type	with screw locking
Series	HPR-B10
Cable outlet	straight
Pg screw connection	none

Dimensions

Dimensional drawing	
Width	58 mm
Height	100.5 mm
Length	145 mm

Material specifications

Color	black
Housing surface material	Powder-coated, black
Material of locking screw	Stainless steel
Impact strength	IK09
Housing material	die-cast aluminum

Ambient conditions

Degree of protection	IP66
	IP68 (0.5 bar / 24 h)
	IP69 (ISO 20653:2013-02)
Impact strength	IK09
Ambient temperature (operation)	-40 °C ... 125 °C

Mechanical properties

Housing - HC-HPR-B10-HHWH-1TTM32-EM-BK



1411067

<https://www.phoenixcontact.com/gb/products/1411067>

Mechanical data

Type of the screw connection	1x M32
Locking type	Screw

Mounting

Assembly instructions	M6 locking screw, slotted hexagon head screw (SW10), tightening torque: 4 Nm
-----------------------	---

Housing - HC-HPR-B10-HHWH-1TTM32-EM-BK


1411067

<https://www.phoenixcontact.com/gb/products/1411067>



Drawings

Dimensional drawing



Dimensional drawing

Housing - HC-HPR-B10-HHWH-1TTM32-EM-BK



1411067

<https://www.phoenixcontact.com/gb/products/1411067>

Approvals

DNV

Approval ID: TAE000037S



EAC

Approval ID: RU C-DE.AI30.B.01102



EAC

Approval ID: RU C-DE.BL08.B.00511

1411067

<https://www.phoenixcontact.com/gb/products/1411067>

Classifications

ECLASS

ECLASS-9.0	27440202
ECLASS-10.0.1	27440202
ECLASS-11.0	27440202

ETIM

ETIM 8.0	EC000437
----------	----------

UNSPSC

UNSPSC 21.0	31261500
-------------	----------

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

1411067

<https://www.phoenixcontact.com/gb/products/1411067>

Accessories

Cable gland

Cable gland - G-INS-M32-M68N-PNES-GY - 1411127

<https://www.phoenixcontact.com/gb/products/1411127>



Cable gland, cable gland material: PA, external cable diameter 15 mm ... 21 mm, shielding: no, connecting thread: M32 x 1.5, color: silver-gray RAL 7001

Cable gland

Cable gland - G-INS-M32-M68N-PNES-BK - 1411136

<https://www.phoenixcontact.com/gb/products/1411136>



Cable gland, cable gland material: PA, external cable diameter 15 mm ... 21 mm, shielding: no, connecting thread: M32 x 1.5, color: jet black RAL 9005

Housing - HC-HPR-B10-HHWH-1TTM32-EM-BK



1411067

<https://www.phoenixcontact.com/gb/products/1411067>

Cable gland

Cable gland - G-INS-M32-M68N-NNES-S - 1411166

<https://www.phoenixcontact.com/gb/products/1411166>



Cable gland, cable gland material: Nickel-plated brass, external cable diameter 15 mm ... 21 mm, shielding: no, connecting thread: M32 x 1.5, color: silver, with O-ring

Cable gland

Cable gland - HC-M-KV-M32(19-27) - 1646010

<https://www.phoenixcontact.com/gb/products/1646010>



Metal screw connection up to 5 bar, thread length: 8 mm, cable diameter: 19 - 27 mm, WAF 43, screw connection: M32

Housing - HC-HPR-B10-HHWH-1TTM32-EM-BK



1411067

<https://www.phoenixcontact.com/gb/products/1411067>

Cable gland

Cable gland - G-INSEC-M32-M68N-NCRS-S - 1411191

<https://www.phoenixcontact.com/gb/products/1411191>



Cable gland, cable gland material: Nickel-plated brass, external cable diameter 14 mm ... 21 mm, shielding: yes, connecting thread: M32 x 1.5, color: silver, with O-ring

Cable gland

Cable gland - HC-M-KV-Z-M32 - 1646162

<https://www.phoenixcontact.com/gb/products/1646162>



Metal screw connection with strain relief clamp, thread length: 8 mm, cable sealing area: 18 - 27 mm, clamping area: 19 - 30 mm, SW 40, screw connection: M32

Housing - HC-HPR-B10-HHWH-1TTM32-EM-BK



1411067

<https://www.phoenixcontact.com/gb/products/1411067>

Cable gland

Cable gland - HC-M-KV-T-M32 - 1646201

<https://www.phoenixcontact.com/gb/products/1646201>

Metal screw connection with cable bend protection and strain relief, thread length: 8 mm, cable sealing area: 18 - 27 mm, clamping area: 20 - 30 mm, SW 40, screw connection: M32



Reducing adapter

Reducing adapter - REDUC-M-KV-M32/M25 - 1647637

<https://www.phoenixcontact.com/gb/products/1647637>

Reducing adapter, material: Brass, nickel-plated, connecting thread: M32 x 1.5, color: silver, with O-ring



Housing - HC-HPR-B10-HHWH-1TTM32-EM-BK



1411067

<https://www.phoenixcontact.com/gb/products/1411067>

Extension adapter

Extension adapter - ENLAR-M-KV-M32/M40 - 1647682

<https://www.phoenixcontact.com/gb/products/1647682>

Step-up adapter, M32 to M40, including O-ring



Screw plug

Screw plug - HC-M-BS-M32 - 1645862

<https://www.phoenixcontact.com/gb/products/1645862>

Screw plug, cable gland material: Nickel-plated brass, connecting thread: M32 x 1.5, color: silver



Phoenix Contact 2022 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk