NSYS3D101230DP

Wall mounted steel enclosure, Spacial S3D, double plain door, with mounting plate, 1000x1200x300mm, IP55, IK10





Main	
Range	Spacial
Product name	Spacial S3D
Application	Multi-purpose
Category	Compact enclosure
Enclosure nominal height	1000 mm
Enclosure nominal width	1200 mm
Enclosure nominal depth	300 mm
Door type	Plain
Mounting plate description	Plain
Type of gland plate	Standard
Installation accessory type	Wall-mounting
Device composition	1 body 2 cable gland plate

2 door with lock1 mounting plate

Complementary

- Compression y		
Body type	Gutter-shaped front rail double sheet thickness Single piece body	
Number of doors	Front face: 2 door(s)	
Door opening side	Reversible (120 °)	
Lock type	3 points lock, 3 mm double-bar	
Accessibility for operation	Front	
Removable parts	Door by hinges Cable gland plate by screws Mounting plate by fixing element	
Material	Enclosure: steel Mounting plate: galvanised steel	
Surface finish	Enclosure: epoxy-polyester powder	
Colour	Enclosure: grey (RAL 7035)	
Standards	IEC 62208	
Product certifications	DNV LR CUL GL BV UL	
Product weight	75 kg	

Environment

IK degree of protection	IK10 conforming to IEC 62262
IP degree of protection	IP55 conforming to IEC 60529

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	35.5 cm
Package 1 Width	102 cm
Package 1 Length	123 cm
Package 1 Weight	72.8 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	2
Package 2 Height	116 cm
Package 2 Width	80 cm
Package 2 Length	122 cm
Package 2 Weight	158 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	☐ Product Environmental Profile

Contractual warranty