



Main

Range of product	Thorsman
Product or component type	Nail plug
Device short name	TPS
Provided equipment	Screw
Drilling diameter	6 mm
Minimum drilling depth	42 mm
Screw diameter	3.5 mm

Complementary

Colour tint	Clear
Material	Nail plug: PA (polyamide) Screw: steel electroplated
Practical load capacity	Shear: 0.4 kN for concrete C25 4.5) Pull-out load: 0.2 kN for concrete C25 6) Shear: 0.4 kN for solid brick 4.5) Pull-out load: 0.2 kN for solid brick 6) Shear: 0.1 kN for low density concrete 500 and expanded clay 4.5) Pull-out load: 0.07 kN for low density concrete 500 and expanded clay 6)
Thickness	0...5 mm fixture
Ambient air temperature for operation	-40...80 °C
Diameter	10 mm
Length	60 mm



Environment

Quantity per set	Set of 100
Net weight	0.0038 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.0 cm
Package 1 Width	1.0 cm
Package 1 Length	6.0 cm
Package 1 Weight	3.71 g
Unit Type of Package 2	BB1
Number of Units in Package 2	100
Package 2 Height	5.8 cm
Package 2 Width	7.6 cm
Package 2 Length	11.8 cm
Package 2 Weight	372.0 g

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Environmental Disclosure	 Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------