



Pan-Ty® PLT.6SM-C0 Cable Tie, Black, UV PA6.6, 2.8"L, 8lb, PK100

PLT.6SM-C0

Panduit PLT.6SM-C0 Locking Cable Ties are designed to satisfy the needs of weather resistant applications, while delivering consistent performance and reliability. Featuring a curved tip to allow for easy pick up from flat surfaces and faster initial threading. Subminiature cross section, 2.8" (71mm) length. Made of Weather Resistant Nylon 6.6 with high resistance to ultraviolet light, are black in color and come in packages of 100.

Specifications

Product Type	Premium Cable Tie
Color	Black
Environment	Indoor/Outdoor
Material	Weather Resistant Nylon 6.6
Resistance Properties	UV Resistant
Overall Length (In.)	2.8
Overall Length (mm)	71
Body Width (In.)	0.07
Body Width (mm)	1.8
Body Thickness (In.)	0.03
Body Thickness (mm)	0.8
Maximum Bundle Diameter (In.)	0.6
Maximum Bundle Diameter (mm)	15
Minimum Bundle Diameter (In.)	0.01
Minimum Bundle Diameter (mm)	0.3
Minimum Loop Tensile Strength (N)	36
Minimum Loop Tensile Strength (lb)	8
Maximum Operating Temperature (°C)	85
Maximum Operating Temperature (°F)	185
Minimum Operating Temperature (°C)	-60
Minimum Operating Temperature (°F)	-76
Minimum Installation Temperature (°C)	-20
Minimum Installation Temperature (°F)	-4
Standards Met	UL Recognized (File #E56854), UL 62275 Compliant (Type 1, 11), RoHS Compliant
For Use With	GTS-E, PTS

Specifications (continued)

Part Features	One-piece locking wedge for consistent performance and reliability. Low thread force and high loop tensile strength.
---------------	--

Packaging Detail

UPC	07498356035
Std. Pkg. Qty.	100
Std. Pkg. Volume (cf)	0.0182
Std. Ctn. Qty.	1000
Std. Ctn. Volume (cf)	0.1824