


#### 19MM Stainless Steel Illuminated




MPZI019

Blue Illumination  
 20 cm lead  
 Flathead




#### 19MM Stainless Steel Non Illuminated



MPZ019

Non Illumination  
 20 cm lead  
 Flathead



#### Specification

#### MPZ019, MPZI019


Type	Momentary
Material	Stainless Steel (Aluminium upon request)
Maximum Voltage	24V AC/DC
Switch Resistance "ON"	<1Ω
Switch Resistance "OFF"	5MΩ
Capacitance	100pF
Switching current (momentary)	1A Max
Switching current (prolonged)	300 mA
Switching pulse time (momentary)	up to 0.3 sec
Switching pulse time (prolonged)	up to 6 sec
LED Illumination	24V AC/DC
Actuating force, typically	3-5 N
Life cycle	10 Million

#### Environmental specs

Sealing	IP68; IP69K
Operating temperature	-40°C to +85°C
Vibration Resistances	5-500Hz/9.4m
Shock resistance	75g (g-force)
RoHS compliance	Compliant


#### Circuit Specification

##### 19MM Stainless Steel Non Illuminated



Switch voltage	24V AC/DC
Switch Current	1A Max
Power Supply	24V AC/DC

##### 19MM Stainless Steel Illuminated



Switch voltage	24 V AC/DC
Switch Current	1A Max
Colour* Illuminated	24V AC/DC
Power Supply	24V AC/DC