# **KNIPEX MultiStrip 10 Automatic Insulation Stripper**

12 42

Stripping without re-adjustment from 0.03 to 10 mm<sup>2</sup> Universal blade geometry – robust and more durable Ideal grip design with excellent haptics Recessed wire cutter

- > fully automatic adjustment to all single-, multi- and fine-stranded conductors with PVC insulation and a number of special insulation throughout the entire capacity range from 0.03 to 10 mm<sup>2</sup>
- > no manual fine adjustment necessary, no damage to the conductors
- > the clamping jaws made of steel hold the cable in a way that prevents slipping without damaging the remaining insulation
- > with recessed wire cutter for copper and aluminium conductors, multi-stranded up to 10 mm<sup>2</sup> and single-stranded up to 6 mm<sup>2</sup>
- > particularly smooth-running mechanics and very low weight
- > replaceable blades block and length stop
- > handle with soft-plastic zone for a steady grip
- > body: plastic, fibreglass-reinforced
- > blade: special tool steel, oil-hardened





Wire cutter for multiple stranded wire cables up to 10 mm<sup>2</sup>



Steel clamping jaws avoid skidding of the



Mode of operation of straight

range are used.


cutters

Patented mechanics

The incision depth of the stripping blade adjusts fully automatically to the diameter of the wire and accordingly also to the thickness of all standard insulating materials. There is no need for any manual adjustment which is still necessary when other conventional pliers with a wide wire-stripping

An incision is made in the red area only.

Not suitable for highly-flexible or armoured insulation materials or for multi-layered insulation.





Precise stripping from 0.03 to 10 mm<sup>2</sup> without re-adjustment

# MultiStrip





Article No.	EAN 4003773-	<b>←→</b> mm		Stripping capacities mm <sup>2</sup>	AWG	ΔΔ g
12 42 195	054580	195	MM	0.03 - 10	32 - 7	136

12 42 195	054580	195 MM	0.03 - 10	32 - 7	136
12 49 21	057581	Spare blades block for 12 42 195			
12 49 23	057604	Spare length stop for 12 42 195			

# Crimp Assortments for end sleeves (ferrules)

**97** 90





- > in a TANOS MINI-systainer® (solid plastic box)
- > T-Loc fastener for one-handed operation: open or close the systainer® with one turn and connect to a second systainer®
- > opening when connected: fast and simple access to content without disconnection
- > two stackable plastic inserts with 6 trays each for connectors
- > with an assortment of end sleeves (ferrules) with / without collar

# 97 90 05

with Crimping Pliers for end sleeves 97 71 180

## 97 90 06

with Crimping Pliers for end sleeves 97 71 180

# 97 90 09

with Self-Adjusting Crimping Pliers for End Sleeves (ferrules) 97 53 04

#### 07 00 10

with Self-Adjusting Insulation Stripper 12 40 200; with Self-Adjusting Crimping Pliers for End Sleeves (ferrules) 97 53 04

#### 97 90 12

with Self-Adjusting Insulation Stripper 12 40 200; with Self-Adjusting Crimping Pliers for End Sleeves (ferrules) 97 53 08

#### 97 90 23

with Crimping Pliers "PreciForce" for End Sleeves (ferrules) 97 52 38

#### 97 90 24

with Self-Adapting Universal Insulation Stripper "MultiStrip 10" 12 42 195; with Self-Adjusting Crimping Pliers for End Sleeves (ferrules) 97 53 08



Several boxes can be connected with each other















Article No.	EAN 4003773-	Pliers	200 x mm²	150 x mm <sup>2</sup>	100 x mm <sup>2</sup>	75 x mm²	50 x mm²	40 x mm²	ΔΔ g
97 90 05	025535	97 71 180	0.5 / 0.75 / 1 / 1.5 / 2.5	4/6			10 / 16		930
97 90 06	025542	97 71 180	0.5 / 0.75 / 1 / 1.5	2,5		4/6	10	16	1000
97 90 09	028574	97 53 04	0.5 / 0.75 / 1 / 1.5 / 2.5		4/6		10		1420
97 90 10	046202	97 53 04 / 12 40 200	0.5 / 0.75 / 1 / 1.5 / 2.5		4 / 6		10		1353
97 90 12	048916	97 53 08 / 12 40 200	0.5 / 0.75 / 1 / 1.5 / 2.5		4/6		10		1427
97 90 23	062158	97 52 38	0.5 / 0.75 / 1 / 1.5 / 2.5		4/6				1226
97 90 24	062394	97 53 08 / 12 42 195	0.5 / 0.75 / 1 / 1.5 / 2.5		4/6		10		1348
97 90 00 LE	054009	TANOS MINI-systainer® empty							900

**97** 

97 90 00

with Crimp Grip Pliers 97 00 215 A

## 97 90 01

with Crimping Pliers 97 32 225

#### 97 90 2

with Crimping Pliers PreciForce® 97 52 36 (for insulated terminals and plug connectors)

#### 97 90 22

with Self-Adapting Universal Insulation Stripper "MultiStrip 10" 12 42 195; with Crimping Pliers PreciForce® 97 52 36 (for insulated terminals and plug connectors)

				Cable Connectors				
Article No.	EAN 4003773-		Pliers		Quantity	Cable mm²	∆'∆ g	
97 90 00	025375		_		25	4 - 6		
	023373		10 2	Blade Terminal Sockets, 6.3 x 0.8 mm	25	1.5 - 2.5	1391	
					25	0.5 - 1		
			07.00.215.4	Round Sockets, Ø 4 mm	25	0.5 - 1		
			97 00 215 A		25	0.5 - 1		
				Cable Connectors, eye type, Ø 4 mm	25	1.5 - 2.5		
		0			25	1.5 - 2.5		
		1		Cable Connectors, eye type, Ø 5 mm	25	4 - 6		
				Cable Connectors, eye type, Ø 6 mm	25	4 - 6		
				Butt Connectors, insulated, red	25	0.5 - 1		
				Butt Connectors, insulated, blue	25	1.5 - 2.5		
				Round Pin Plugs, Ø 4 mm	25	0.5 - 1		
7 90 21	062134	_		-	25	0.5 - 1		
90 21	062134	<b>™</b> ww		Blade Terminal Sockets, 6.3 x 0.8 mm	25	1.5 - 2.5	-	
				Cable Connectors, eye type, Ø 4 mm	25	0.5 - 1	-	
				Cable Connectors, eye type, Ø 5 mm	25	0.5 - 1		
		5	97 52 36	Cable Connectors, eye type, Ø 6 mm	25	4 - 6	-	
			37 32 30	Cable Connectors, eye type, Ø 8 mm	25	4 - 6	-	
				Cable Connectors, eye type, Ø 4 mm	25	1.5 - 2.5	141	
				Cable Connectors, eye type, Ø 5 mm	25	1.5 - 2.5		
				Cable Connectors, eye type, Ø 6 mm	25	1.5 - 2.5	-	
				Butt Connectors, insulated, red	25	0.5 - 1	-	
					25	4 - 6	-	
				Butt Connectors, insulated, blue			-	
				Butt Connectors, insulated, yellow	25	1.5 - 2.5		
90 22	062141			Blade Terminal Sockets, 6.3 x 0.8 mm	25	0.5 - 1	_	
					25	1.5 - 2.5		
				Cable Connectors, eye type, Ø 4 mm	25	0.5 - 1		
				Cable Connectors, eye type, Ø 5 mm	25			
			07.50.26	Cable Connectors, eye type, Ø 4 mm	25	1.5 - 2.5		
			97 52 36 12 42 195	Cable Connectors, eye type, Ø 5 mm	25	1.5 - 2.5	152	
				Cable Connectors, eye type, Ø 6 mm	25	1.5 - 2.5		
					25	4 - 6		
				Cable Connectors, eye type, Ø 8 mm	25	4 - 6		
				Butt Connectors, insulated, red	25	0.5 - 1		
				Butt Connectors, insulated, blue	25	1.5 - 2.5		
				Butt Connectors, insulated, yellow	25	4 - 6		
7 90 25	076971	MU		Non-insulated Blade Terminal Sockets	25	0.5 - 1.5		
				6.3 x 0.8 mm	25	1 - 2.5		
				Blade Terminal Sockets	25	0.5 - 1		
			97 22 240	6.3 x 0.8 mm	25	1.5 - 2.5	1150	
				515 X 516 11111	25	4 - 6		
				Blade Terminal Plugs	25	0.5 - 1		
				6.3 x 0.8 mm	25	1.5 - 2.5		
				Cable Connectors are time (1.4 mm	25	0.5 - 1		
				Cable Connectors, eye type Ø 4 mm	25	1.5 - 2.5		
				Butt Connectors, insulated, red	25	0.5 - 1		
				Butt Connectors, insulated, blue	25	1.5 - 2.5	1	
				Butt Connectors, insulated, yellow	25	4 - 6	1	