# PCJ-105D3M,301 ✓ ACTIVE

## OEG | OEG Miniature PCB Relay PCJ

TE Internal #: 1721081-2

OEG Miniature PCB Relay PCJ, Power Relays, Standard,


Monostable, DC, 150 – 200mW Coil Power Rating Class, 200mW


Coil Power Rating DC

View on TE.com >





Relays, Contactors & Switches > Relays > Power Relays











Power Relay Type: Standard

Coil Magnetic System: Monostable, DC
Coil Power Rating Class: 150 – 200 mW

Coil Power Rating DC: 200 mW

Coil Resistance: 125  $\Omega$ 

## **Features**

# **Product Type Features**

Power Relay Type	Standard
Electrical Characteristics	
Insulation Initial Dielectric Between Coil & Contact Class	3500 – 4000 V
Insulation Initial Dielectric Between Open Contacts	750 Vrms
Contact Limiting Making Current	3 A
Contact Limiting Short-Time Current	3 A
Contact Limiting Continuous Current	3 A
Insulation Creepage Class	5.5 – 8 mm
Insulation Initial Dielectric Between Contacts & Coil	4000 Vrms
Insulation Initial Resistance	1000 ΜΩ
Insulation Creepage Between Contact & Coil	8 mm[.315 in]
Contact Limiting Breaking Current	3 A
Coil Magnetic System	Monostable, DC
Coil Power Rating Class	150 – 200 mW



Coil Power Rating DC	200 mW
Coil Resistance	125 Ω
Coil Special Features	UL Coil Insulation Class A
Coil Voltage Rating	5 VDC
Contact Switching Load (Min)	100mA @ 5V
Contact Switching Voltage (Max)	30 VDC
Contact Voltage Rating	250 VAC
Body Features	
Insulation Special Features	7000V Initial Surge Withstand Voltage between Contacts & Coil
Product Weight	4 g[.141 oz]
Contact Features	
Contact Arrangement	1 Form A (NO)
Contact Current Class	2 – 5 A, 16 A
Contact Current Rating (Max)	3 A
Contact Material	AgNi
Contact Number of Poles	1
Terminal Type	PCB-THT
Mechanical Attachment	
Relay Mounting Type	Printed Circuit Board
Dimensions	
Length Class (Mechanical)	20 – 25 mm
Insulation Clearance Class	5 – 8 mm
Height Class (Mechanical)	14 – 15 mm
Insulation Clearance Between Contact & Coil	7.5 mm[.295 in]
Width Class (Mechanical)	6 – 8 mm
Product Width	7 mm[.276 in]
Product Length	20.39 mm[.803 in]

# Usage Conditions

Product Height

Environmental Ambient Temperature Class	70 – 85 °C
Environmental Ambient Temperature (Max)	85 °C[185 °F]
Environmental Category of Protection	RTII

15.01 mm[.591 in]



### **Packaging Features**

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2020 (205) Candidate List Declared Against: JAN 2020 (205) Does not contain REACH SVHC
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2020 (205) Candidate List Declared Against: JAN 2020 (205)
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Also in the Series | OEG Miniature PCB Relay PCJ





# Customers Also Bought





















# **Documents**

# **Product Drawings**

PCJ-105D3M,301

English

### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1721081-2\_F.2d\_dxf.zip



English

**Customer View Model** 

ENG\_CVM\_CVM\_1721081-2\_F.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1721081-2\_F.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

PCJ Series Relay Data Sheet English

English

**Product Specifications** 

**Definitions Relays** 

English

**Product Specification** 

Japanese

**Product Environmental Compliance** 

**TE Material Declaration** 

English