

tesa® 4651

Premium acrylic coated cloth tape

PRODUCT INFORMATION

Product Description

tesa® 4651 is a powerful high quality acrylic coated cloth tape. It is based on a 148 mesh woven rayon fabric backing and a natural rubber adhesive.

tesa® 4651 is a very strong cloth tape for almost every application.

Features:

- high adhesion even on rough surfaces
- excellent tensile strength
- straight tear edges longitudinal and horizontal
- easy to write on
- conformable
- available in 8 colors: black, white, grey, yellow, blue, red, green, brown

Main Application

- Bundling and reinforcing of heavy pipes, profiles etc
- Covering of bore holes and other openings
- Marking of wires and cables
- Labelling and colour coding
- Floor marking
- Airtight and permanent sealing of pipes
- Securing of sharp edges
- Fixing and insulating of wires
- Sealing of tins and tubes
- Floor coating
- Sandblasting
- ... and a lot more!

Technical Data

 Backing material acrylic-coated cloth Total thickness

310 µm Type of adhesive natural rubber

Adhesion to steel

Elongation at break 13 %

Tensile strength 100 N/cm 130 °C Temperature resistance (30 min)

Mesh 148 count per square inch

Properties

Hand tearability Suitable for die cutting yes Straight tear edges Abrasion resistance

++ ++ Easy to write on Water resistance yes

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

3.3 N/cm

Additional Info

Complies with LV 312-1 Dialectric strength.

For latest information on this product please visit http://l.tesa.com/?ip=04651

Page 1 of 1 / As of 08/07/14

tesa SE

Quickbornstraße 24 20253 Hamburg

Germany Phone: +49 (40) 4909 101

5825 Carnegie Boulevard Charlotte, N.C. 28209 United States of America Phone: +1 (704) 554 0707 Tel: +65 6697 9888 Fax: +1 (704) 553 5634 Fax: +65 6659 6390 http://www.tesatape.com http://www.tesa-asia.com

tesa tape inc.

tesa tape Asia Pacific Pte. Ltd.

9 North Buona Vista Drive #04-01 The Metropolis Tower 1 Singapore 138588

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.