



Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	15 A
Voltage Rating	120 V AC
Mounting Type	Plug-in
Number of Poles	1P
Circuit Breaker Type	Ground fault protecting class A 6 mA
Ratings	Not rated
Electrical Connection	Pressure plate

Complementary

Interrupt Rating	10 kA at 120 V AC 50/60 Hz
Number of Panel Spaces	1
Wire Size	AWG 14...AWG 8 copper AWG 12...AWG 8 aluminium
Tightening Torque	4.6 N.M for 2.5...10 mm ² (AWG 16...AWG 14) 4.6 N.m for 4...20 mm ² (AWG 12...AWG 4)
Height	105 mm
Width	19 mm
Depth	74 mm
Net weight	0.227 kg

Environment

Certifications	UL listed CSA
Ambient Rating	40 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.16 cm
Package 1 Width	3.56 cm
Package 1 Length	13.72 cm
Package 1 Weight	231.34 g
Unit Type of Package 2	CAR
Number of Units in Package 2	38
Package 2 Height	10.922 cm
Package 2 Width	35.814 cm
Package 2 Length	53.086 cm
Package 2 Weight	9.253 kg
Unit Type of Package 3	PAL
Number of Units in Package 3	1824
Package 3 Height	101.6 cm
Package 3 Width	101.6 cm

Package 3 Length	121.92 cm
Package 3 Weight	447.242 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------