



Main

| | |
|---------------------------|--|
| Range | MasterPact |
| Device short name | XF |
| Product or component type | Voltage release |
| Device application | Control |
| Range compatibility | Masterpact (MasterPact MTZ2) circuit-breaker Masterpact (MasterPact MTZ3) circuit-breaker |
| Voltage release type | Closing coil |







Complementary

| | |
|-------------------------------|--|
| Control type | Standard |
| [Un] voltage power supply | 48 V AC 50/60 Hz 48...60 V DC |
| Threshold tripping voltage | 0.85...1.1 Un on closing |
| Holding power consumption | 4.5 W |
| Circuit breaker mounting mode | Drawout |
| Maximum response time | 80 ms on closing for MasterPact MTZ2 90 ms on closing for MasterPact MTZ3 |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 3.5 cm |
| Package 1 Width | 6.0 cm |
| Package 1 Length | 8.3 cm |
| Package 1 Weight | 1.164 kg |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| EU RoHS Directive | Compliant  EU RoHS Declaration |
| Mercury free | Yes |
| China RoHS Regulation |  China RoHS Declaration |
| RoHS exemption information |  Yes |
| Environmental Disclosure |  Product Environmental Profile |
| Circularity Profile |  End Of Life Information |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 Monate |
|----------|-----------|