# NSYTBS111113H

ABS box IP66 IK07 RAL7035 Int.H105W105D125 Ext.H116W116D133 Opaque cover H80





#### Main

| Range               | Thalassa                               |
|---------------------|--|
| Product name        | Thalassa TBS                           |
| Device application  | Multi-purpose                          |
| Category            | Industrial box                         |
| Height              | 116 mm                                 |
| Width               | 116 mm                                 |
| Depth               | 133 mm                                 |
| Internal height     | 105 mm                                 |
| Internal width      | 105 mm                                 |
| Internal depth      | 125 mm                                 |
| Enclosure mounting  | Wall mounted                           |
| Device composition  | 1 body                                 |
|                     | 1 cover                                |
|                     | 4 cover screw                          |
| Quantity per set    | Set of 2                               |
| Body type           | One piece moulded                      |
| Type of front cover | High plain cover                       |
| Cover fixing        | Plastic screws                         |
| Lock type           | Captive screw flat outside sealed area |
| Removable parts     | Cover by captive screws                |
|                     |  |

## Complementary

| ,                                   |                                       |  |
|-------------------------------------|---------------------------------------|--|
| Material                            | ABS (acrylonitrile butadiene-styrene) |  |
| Colour                              | Grey (RAL 7035)                       |  |
| Standards                           | IEC 62208                             |  |
| Product certifications              | TÜV                                   |  |
| Electrical insulation class         | Class II                              |  |
| IP degree of protection             | IP66 conforming to NEMA 4.4X          |  |
| IK degree of protection             | IK07 conforming to IEC 62262          |  |
| Glow wire resistance                | 650 °C conforming to IEC 60695-2-11   |  |
| Ambient air temperature for storage | -1540 °C                              |  |
| Operating temperature               | -2560 °C                              |  |
| Product weight                      | 0.24 kg                               |  |
|                                     |                                       |  |

### **Packing Units**

| Unit Type of Package 1       | PCE   |  |
|------------------------------|-------|--|
| Number of Units in Package 1 | 1     |  |
| Package 1 Height             | 12 cm |  |
| Package 1 Width              | 12 cm |  |
| Package 1 Length             | 34 cm |  |
| Package 1 Weight             | 240 g |  |

### Offer Sustainability

| Sustainable offer status   | Green Premium product   |
|----------------------------|---|
| REACh Regulation           | ☑ REACh Declaration   |
| REACh free of SVHC         | Yes   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS  Declaration |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| China RoHS Regulation      | ☑ China RoHS Declaration  |
| RoHS exemption information | ₽¥Yes   |
| Environmental Disclosure   | Product Environmental Profile   |
|                            |   |

### Contractual warranty

| Warranty | 18 months |
|----------|-----------|
| wantanty | TO MONUIS |