# NSYS3D4625P

Spacial S3D plain door with mount.plate. H400xW600xD250 IP66 IK10 RAL7035.





### Main

Range	Spacial
Product name	Spacial S3D
Application	Multi-purpose
Category	Compact enclosure
Enclosure nominal height	400 mm
Enclosure nominal width	600 mm
Enclosure nominal depth	250 mm
Door type	Plain
Mounting plate description	Plain
Type of gland plate	Standard
Installation accessory type	Wall-mounting
Device composition	body mounting plate door with lock cable gland plate

#### Complementary

But it		
Body type	Gutter-shaped front rail double sheet thickness Single piece body	
Number of doors	Front face: 1 door(s)	_
Door opening side	Reversible (120 °)	
Lock type	3 points lock, 3 mm double-bar	
Accessibility for operation	Front	
Removable parts	Door by hinges Cable gland plate by screws Mounting plate by fixing element	
Material	Enclosure: steel Mounting plate: galvanised steel	
Surface finish	Enclosure: epoxy-polyester powder	
Colour	Enclosure: grey (RAL 7035)	
Standards	IEC 62208	
Product certifications	GL BV LR UL DNV cUL	
Product weight	14.5 kg	

### Environment

NEMA degree of protection	NEMA 4X/13
IK degree of protection	IK10 conforming to IEC 62262
IP degree of protection	IP66 conforming to IEC 60529

# Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	30.0 cm
Package 1 Width	42.0 cm
Package 1 Length	61.5 cm
Package 1 Weight	14.2 kg
Unit Type of Package 2	PAM
Number of Units in Package 2	27
Package 2 Height	199.0 cm
Package 2 Width	100.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	397.3 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	☐ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile

## Contractual warranty

Warranty	18 months