GS2AH350

External rotary handle, TeSys GS, black handle, left side mounting, 2 positions I-O, IP65, for GS 630 to 1250A IEC

Main

Range of product	TeSys
Range	TeSys
Device short name	GS2AH
Product or component type	Rotary handle
Range compatibility	TeSys (TeSys GS) GS2S TeSys (TeSys GS) GS2T TeSys (TeSys GS) GS2V
Type of operating handle	External left side
Handle colour	Black
Handle front plate colour	Grey

Complementary

Handle positions	O-I
Rotary handle padlocking	Lockable in O position
Switch rated current	630 A 800 A 1250 A
Standards	IEC
Net weight	0.28 kg

Environment

IP degree of protection	IP65

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.0 cm
Package 1 Width	9.0 cm
Package 1 Length	27.0 cm
Package 1 Weight	280.0 g

Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months