### FASTIN-FASTON | FASTIN-FASTON 250

TE Internal #: 6-160448-2

FASTIN-FASTON 250, Quick Disconnects, Receptacle, 17 – 13

AWG, 1.03 – 2.62 mm<sup>2</sup>, Mating Tab Width 6.35 mm [.25 in]

View on TE.com >



Terminals & Splices > Quick Disconnects











Terminal & Splice Type: Receptacle

Wire Size: 1.03 – 2.62 mm<sup>2</sup>

Mating Tab Width: 6.35 mm [.25 in]

Mating Tab Thickness: .81 mm [.032 in]

## **Features**

### **Product Type Features**

Wire/Cable Type	Regular Wire
Wire Stop	No
Terminates To	Wire & Cable
Insertion Force	Normal
Sealable	No
Insulated	No
Configuration Features	
Connection Capacity	Single
Electrical Characteristics	
Voltage (Max)	250 V

# **Body Features**

Fully Insulated	No
Plating Material	Tin

### **Contact Features**

Terminal Type Receptacle
--------------------------



Terminal & Splice Type	Receptacle
Terminal Orientation	Straight
Contact Base Material	Phosphor Bronze
Crimp Type	F-Crimp
Barrel Type	Open
Mechanical Attachment	
Mating Retention Type	Locking Lance
Locking Lance Height	.32 mm
Wire Insulation Support	With
Dimensions	
Accepts Wire Insulation Diameter Range	3.43 – 5.08 mm[.135 – .2 in]
Overall Length	19.2 mm[.755 in]
Receptacle Terminal Stock Thickness	.33 mm[.013 in]
Wire Size	1.03 – 2.62 mm <sup>2</sup>
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Usage Conditions	
Operating Temperature Range	-40 - 110 °C[-40 - 230 °F]
Industry Standards	
UL Flammability Rating	UL 94V-2
Packaging Features	
Packaging Quantity	5000
Packaging Method	Strip/Reel
Other	
Comment	"According to DIN 46340, Part 3", Chamfered, Without Dimple

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold




EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2020 (205) Candidate List Declared Against: JAN 2020 (205) Does not contain REACH SVHC
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2020 (205) Candidate List Declared Against: JAN 2020 (205)
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

# **Compatible Parts**













TE Model / Part # 2-2150314-2 OCEAN\_2.0\_Applicator-E-110F180FA



TE Model / Part # 2-2150427-1 OCEAN\_2.0\_APPLICATOR-E-110F140OV



TE Model / Part # 2-2150427-2 OCEAN\_2.0\_APPLICATOR-E-110F140OVA



TE Model / Part # 2150314-1 OCEAN\_2.0\_Applicator-E-110F180F




TE Model / Part # 2150314-2 OCEAN\_2.0\_Applicator-E-110F180FA



TE Model / Part # 2150427-1 OCEAN\_2.0\_APPLICATOR-E-110F140OV



TE Model / Part # 2150427-2 OCEAN\_2.0\_APPLICATOR-E-110F140OVA




TE Model / Part # 7-2150427-7 OCEAN\_2.0\_SPARE\_PART\_KIT-110F140OV

# Also in the Series | FASTIN-FASTON 250



Crimp Terminal Housings(214)




Quick Disconnects(253)


# Customers Also Bought



TE Model / Part #160913-4 FF 250 REC 2.5-4.0MM2 TPPB



TE Model / Part #5-160446-2 FF 250 REC 1.0-2.5MM2 TPPB



TE Model / Part #925176-5 FF 312 3P HOUSING REC POLYAMID 6.6 BLACK



TE Model / Part #967011-1 EINZELADERDICHTUNG

# **Documents**

**Product Drawings** FF 250 REC 1.0-2.5MM2 TPPB

English

**CAD Files** 

3D PDF

3D



**Customer View Model** 

ENG\_CVM\_CVM\_6-160448-2\_AR.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_6-160448-2\_AR.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_6-160448-2\_AR.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

1654742\_HOUSEHOLD\_APPLIANCES\_RAST5

English

**Product Specifications** 

EB\*\*General Application Specification for Open Barrel Terminals

English

**Application Specification** 

English