



Innen-Ø / inner Ø	Ø nach Schrumpfung / Ø after shrinking	Farbe / color	Länge / length	Stück / pieces
1,6 mm	0,5 mm	rot / red	32 mm	40
2,4 mm	0,8 mm	blau / blue	32 mm	30
3,2 mm	1,0 mm	gelb / yellow	32 mm	20
4,8 mm	1,6 mm	grün / green	65 mm	10
6,4 mm	2,2 mm	transparent	65 mm	6
7,9 mm	2,7 mm	braun / brown	65 mm	5
9,5 mm	3,2 mm	weiß / white	95 mm	4
12,7 mm	4,2 mm	schwarz / black	95 mm	3

✓ RoHS ✓ REACH

Shrink tube assortment Shrink tube assortment

shrinking ratio 3:1, colored (with adhesive)

Order-No. N1807CA005

Application / Description

Comprehensive Assortment box consisting of 118 pcs heat shrink tubing with a shrink ratio of 3:1. This set includes different colors and sizes from 1.6 to 12.7 mm. The adhesive inside the tubing melts during shrinking process, ensuring a firm grip. Ideal for insulation, as a mechanical and anti kink protection or protection against corrosion in the area of repair and maintenance as well as hobbies and do-it-yourself projects.



Add-on information

Shrinking ratio: 3:1
 Material: PE
 Shrinking temperature: 70°C - 125°C
 Operation temperature: -40°C - 125°C
 Flammability: VW-1
 Tensile strength: $\geq 10,4$ Mpa
 Elongation at break: $\geq 300\%$
 Rated voltage: 600 V
 Dielectric strength: $\geq 1,5$ kV/mm at 30 sec.

© kabeltronik[®] Arthur Volland GmbH
 Mühlweg 6, 85095 Denkendorf
 Tel.: 08466 - 9404-0
 E-Mail: info@kabeltronik.de