



### Main

Range	Mureva
Range of product	Mureva lights
Product or component type	Floodlight
Device application	Ware-houses and parking garages Residential Media device support Public areas Secure lighting Stadiums and arenas

### Complementary

Type of installation	Outdoor
Total system power	30 W
Light source	LED
[Ue] rated operational voltage	230 V AC
Power factor	0.9
Colour rendering index	R <sub>a</sub> =80
Luminous flux	3000 lm
Bulb lifespan	50000 h
Colour temperature	4000 K
Colour tint	Black
Provided equipment	Sensor
Electrical insulation class	Class F
Beam angle	110 °
Shape	Rectangular
Height	189.4 mm
Width	201.4 mm
Depth	26.5 mm
Net weight	820 g

### Environment

Environmental characteristic	Weatherproof
IP degree of protection	IP44
IK degree of protection	IK04
Ambient air temperature for operation	-30...45 °C

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	21.8 cm
Package 1 Width	21.8 cm
Package 1 Length	21.8 cm
Package 1 Weight	800 g
Unit Type of Package 2	S04

Number of Units in Package 2	10
Package 2 Height	30 cm
Package 2 Width	40 cm
Package 2 Length	60 cm
Package 2 Weight	8.703 kg
Unit Type of Package 3	P12
Number of Units in Package 3	80
Package 3 Height	75 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	81.624 kg

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

### Contractual warranty

Warranty	3 years
----------	---------