Raychem

TE Internal #: 974559-000

SolderSleeve Shield Terminators, Shield Terminator, Expanded Inside Diameter (Min) 4.3 mm [.17 in], Recovered Inside Diameter

(Max) .085 in [2.15 mm]

View on TE.com >



Harnessing > Interconnect Devices > SolderSleeve Shield Terminators



Product Type: Shield Terminator

Expanded Inside Diameter (Min): 4.3 mm [.17 in]

Recovered Inside Diameter (Max): 2.15 mm [.085 in]

Pre-Installed Lead: Yes

Resistance Properties: Immersion Protection

Features

Product Type Features

Splice Type	Shield Terminator
Temperature Indicator Type	Thermochromic
Temperature Indicator	Yes
Product Type	Shield Terminator

Configuration Features

Pre-Installed Lead Type	55A0111
Pre-Installed Lead	Yes

Body Features

Lead Color	Orange
Lead Plating Material	Tin
Lead Stranding	Stranded

Termination Features

Termination Method	Solder	
--------------------	--------	--

Dimensions

Pre-Installed Lead Wire Size	.38 mm²
Dielectric Outside Diameter (Max)	1.25 mm[.05 in]
Shield Outside Diameter (Min)	2.15 mm[.085 in]
Overall Length	16.5 mm[.65 in]



Jacket Outside Diameter	4.3 mm[.17 in]
Expanded Inside Diameter (Min)	4.3 mm[.17 in]
Recovered Inside Diameter (Max)	2.15 mm[.085 in]

Usage Conditions

Resistance Properties	Immersion Protection
Wire Temperature (Max)	105 °C

Industry Standards

Government Qualified	Yes
MIL/NAS Specification (MIL-S-83519, NAS-1747)	AS83519/2

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUN 2020 (209) Candidate List Declared Against: JUL 2019 (201) Pb (37% in Solder) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Customers Also Bought



RECEPT ASSY,15 POSN,AMPLIMITE



TE Model / Part #205561-2 RECEPT ASSY,37 POSN,AMPLIMITE



TE Model / Part #205163-1 RECEPT ASSY,15 POSN,AMPLIMITE



TE Model / Part #721038-000 D-181-1226-90/9



TE Model / Part #955477-000



TE Model / Part #375094-000



TE Model / Part #163665-000



TE Model / Part #866259-000



TE Model / Part #469411-000 0024A0024-9X



TE Model / Part #DTS24F11-35SN **RECP ASSY**

Documents

Product Drawings S02-08-R-3

English

Datasheets & Catalog Pages

1654025_Sec8_B-155_CWT_SO63_S01to03_SO96

English

Raychem Electrical Interconnect Products

English

SolderSleeve Shield Terminators, Shield Terminator, Expanded Inside Diameter (Min) 4.3 mm [.17 in], Recovered Inside Diameter (Max) .085 in [2.15 mm]

