



## Pan-Ty® PLT.6SM-C Cable Tie, PA6.6, 2.8"L, 8lb, PK100

PLT.6SM-C

Panduit PLT.6SM-C Locking Cable Ties are designed to satisfy the needs of general applications, while delivering consistent performance and reliability. Featuring a curved tip to allow for easy pick up from flat surfaces and faster initial threading. Subminiature cross section, 2.8" (71mm) length. Made of Nylon 6.6, are natural in color and come in packages of 100.

### Specifications

Product Type	Premium Cable Tie
Color	Natural
Environment	Indoor
Material	Nylon 6.6
Overall Length (In.)	2.8
Overall Length (mm)	71
Body Width (In.)	0.07
Body Width (mm)	1.8
Body Thickness (In.)	0.03
Body Thickness (mm)	0.8
Maximum Bundle Diameter (In.)	0.6
Maximum Bundle Diameter (mm)	15
Minimum Bundle Diameter (In.)	0.01
Minimum Bundle Diameter (mm)	0.3
Minimum Loop Tensile Strength (N)	36
Minimum Loop Tensile Strength (lb)	8
Maximum Operating Temperature (°C)	85
Maximum Operating Temperature (°F)	185
Minimum Operating Temperature (°C)	-60
Minimum Operating Temperature (°F)	-76
Minimum Installation Temperature (°C)	-20
Minimum Installation Temperature (°F)	-4
Standards Met	UL Recognized (File #E56854), UL 62275 Compliant (Type 1, 11), RoHS Compliant
For Use With	GTS-E, PTS
Part Features	One-piece locking wedge for consistent performance and reliability. Low thread force and high loop tensile strength.

**Packaging Detail**

UPC	07498356032
Std. Pkg. Qty.	100
Std. Pkg. Volume (cf)	0.0182
Std. Ctn. Qty.	1000
Std. Ctn. Volume (cf)	0.1824