

Torque screwdriver set TorqueVario®-S ESD



**mixed, 13 pcs., variably adjustable torque limit,
0,4-1,0 Nm in box**

2882 S10

- | | |
|-------------------------|---|
| Order-No. | (|
| 43898 | 1 |
| <input type="radio"/> O | Torque screwdriver TorqueVario®-S ESD Variable torque limit settings / 0,4-1,0 Nm |
| <input type="radio"/> O | Bit holder clamping with ball for torque screwdriver with long handle |

Adjusting tool for torque screwdriver with long handle

- | | |
|-------------------------|---------------------------------------|
| <input type="radio"/> ⊖ | 4,0 x 25 / 4,5 x 25 |
| <input type="radio"/> + | PH0 x 25 / PH1 x 25 |
| <input type="radio"/> ✕ | PZ0 x 25 / PZ1 x 25 |
| <input type="radio"/> ⚡ | T4 x 25 / T5 x 25 / T6 x 25 / T8 x 25 |

IEC 61340-5-1. DIN EN ISO 6789.

Torque screwdriver TorqueVario®-S ESD



Variable torque limit settings

2882

Order-No.	Nm	+/- %	⊖	⊜	⊟	(
36851	0,04-0,46•	10%	4	127	23	1
26865	0,1-0,6	10%	4	127	23	1
36852	0,1-0,6	6%	4	127	23	1
26629	0,4-1,0	6%	4	127	23	1
26866	0,5-2,0	6%	4	131	30	1
30495	0,8-5,0	6%	4	138	36	1

• Precision in range of 0,1-0,46 Nm.
IEC 61340-5-1. DIN EN ISO 6789.



INFOBOX: Electrostatic conductive ESD tools



Sensitive, electronic components can be damaged even at a very low voltage.

- Dissipative tools by Wiha discharge the electrostatic energy in a controlled, safe manner.
- ESD tools meet the ESD Standard IEC 61340-5-1.
- ESD tool handles have a surface resistance of 10^6 - 10^9 Ohm.