## NSYSM1812402DP

# Spacial SM compact enclosure with mounting plate - 1800x1200x400 mm





#### Main

| Range                       | Spacial   |
|-----------------------------|---|
| Product name                | Spacial SM  |
| Product or component type   | Compact enclosure   |
| Application                 | Multi-purpose   |
| Installation accessory type | Floor-standing  |
| Device composition          | 1 body 2 door 2 cable gland plate 1 locking system with handle: door 1 blocking system: left door 4 mounting plate bracket 1 mounting plate |
| Removable parts             | Door by screws hinge<br>Mounting plate by screws mounting plate bracket<br>Mounting plate bracket by screws                                 |
| Enclosure nominal height    | 1800 mm   |
| Enclosure nominal width     | 1200 mm   |
| Enclosure nominal depth     | 400 mm  |
|                             |   |

#### Complementary

| Complementary               |   |  |
|-----------------------------|---|--|
| Number of doors             | Front: 2 door(s)  |  |
| Door opening side           | Left (120 °)<br>Right (120 °)   |  |
| Door type                   | Plain   |  |
| Lock type                   | 4 points lock, handle with 5 mm double bar insert   |  |
| Body type                   | Front part forming a rigid frame with welded corners Single piece body with welded rear panel |  |
| Mounting plate description  | Plain   |  |
| Type of gland plate         | Standard  |  |
| Cable entry                 | 1 entry   |  |
| Material                    | Mounting plate: galvanised steel<br>Body: sheet steel<br>Door: sheet steel<br>Hinge: zamak    |  |
| Surface finish              | Epoxy-polyester powder  |  |
| Colour                      | Enclosure: grey (RAL 7035)<br>Handle: black (RAL 9005)  |  |
| Accessibility for operation | Front   |  |
| Product weight              | 149.5 kg  |  |
|                             | · · · · · · · · · · · · · · · · · · ·   |  |

#### Environment

| Standards               | IEC 62208                    |  |
|-------------------------|------------------------------|--|
| Product certifications  | UL<br>BV<br>DNV              |  |
| IK degree of protection | IK10 conforming to IEC 62262 |  |
| IP degree of protection | IP55 conforming to IEC 60529 |  |

## Packing Units

| Unit Type of Package 1       | PCE        |
|------------------------------|------------|
| Number of Units in Package 1 | 1          |
| Package 1 Height             | 192.0 cm   |
| Package 1 Width              | 124.0 cm   |
| Package 1 Length             | 48.0 cm    |
| Package 1 Weight             | 147.412 kg |

### Offer Sustainability

| Sustainable offer status   | Green Premium product  |
|----------------------------|--|
| REACh Regulation           | ☑ REACh Declaration  |
| REACh free of SVHC         | Yes  |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) EVEL RoHS Declaration |
| Mercury free               | Yes  |
| China RoHS Regulation      | China RoHS Declaration   |
| RoHS exemption information | ₫Yes   |
| Environmental Disclosure   |  |

## Contractual warranty

| Warranty                              | 10 months |
|---------------------------------------|-----------|
|                                       | 18 months |
| · · · · · · · · · · · · · · · · · · · |           |