



✓ installation ✓ halogen free ✓ FRNC ✓ RoHS ✓ REACH ✓ CE ✓ ✓ ✓ UN/ECE R118

UL AWM Style 11028 - FRNC AWG 26-7

Order-No. 0902607

Application / Description

UL/cUL stranded wires in halogen free and flame retardant construction. The mPPE-material allows very small outer diameters and don't contain softeners. Therefore it's an environment friendly replacement for PVC stranded wires. Stranded wires acc. to UL are primarily used for the internal wiring in electrical equipment as well as electrical control boxes and are steady to a large extent against acids, caustic solutions and many oils.



Variant data

O.D.	approx. 1,05 mm
weight	2,2 kg/km
Cu-weight	1,4 kg/km
skinning tool	20100 / 40025

Construction / data

Conductor	tinned stranded copper wire
Structure of conductor	7x0,16 mm
Conductor dimension	0,14 qmm
Core-Ø	approx. 1,05 mm
AWG	26-7
Core insulation	mPPE
Dimension	AWG 26-7

Technical characteristics

Temperature range	static: -40 °C to +105 °C dynamic: -20 °C to +105 °C
Bending radius static	> 10 x O.D.
Bending radius dynamic	> 15 x O.D.
Operating voltage	600 V
Testing voltage	6.000 V

Insulation resistance > 20 MOhm x km at + 20°C

Packaging

Spools at 250m

Lower and upper lengths according to availability. Special packaging on request.

Add-on information

Advantages of mPPE compared to PVC:

- trend-setting, because environment friendly and recyclebar (non-interlaced thermoplastic)
- small dielectric constant permits substantially smaller outside diameters, thereby weight saving
- higher electrical strength
- larger insulation resistance
- FRNC (LSZH), flame retardant, zero halogen
- fulfills the strong vertical-flame-test VW1 acc. to UL 1581

Colours

The following colors are available:

black, white, red, blue, orange, yellow, green, brown, grey

(further colors as well as 2-colored versions are available on request)

© kabeltronik® Arthur Volland GmbH

Mühlweg 6, 85095 Denkendorf

Tel.: 08466 - 9404-0

E-Mail: info@kabeltronik.de

 **kabeltronik®**