

Alcoswitch | Alcoswitch TPB

TE Internal #: 5-1437571-7

Alcoswitch TPB, Push Button Switches, Single Pole - Single Throw Configuration (Pole-Throw), Switch, Single Actuator, Extended

Actuator Profile

View on TE.com >



Relays, Contactors & Switches > Switches > Push Button Switches



Configuration (Pole-Throw): Single Pole - Single Throw

Push Button Switch Product Type: Switch

Number of Actuators: Single
Actuator Profile: Extended
Bushing Style: Unthreaded

Features

Product Type Features

Switch Type	Pushbutton
Dust Proof	No
Push Button Switch Product Type	Switch
Illuminated	No
Actuator Style	Round

Configuration Features

ESD Grounding Terminal	Without
Ganged	No
Configuration (Pole-Throw)	Single Pole - Single Throw
Number of Actuators	Single
Snap Action	Without
Support Bracket	Without
Tactile	No
Operating Function	NO, Momentary

Electrical Characteristics

Push Button Switch Voltage Rating	20 VDC
-----------------------------------	--------

Body Features

Actuator Force	260 g[9.178 oz]



Case Material	Polyester
Actuator Material	Polyamide
Actuator Profile	Extended
Bushing Style	Unthreaded
Actuator Color	Black
Contact Features	
Contact Base Material	Copper Alloy
Push Button Switch Contact Current Rating	.4 A
Switch Contact Plating Material	Gold over Nickel
Termination Features	
Termination Type	Printed Circuit
Mechanical Attachment	
Mounting Angle	Right Angle
Push Button Switch Mounting Type	Through Hole
Housing Features	
Housing Features Low Profile	No
	No No
Low Profile	
Low Profile Process Sealed	
Low Profile Process Sealed Dimensions	No
Low Profile Process Sealed Dimensions Actuator Length	No 3.48 mm[.137 in]
Low Profile Process Sealed Dimensions Actuator Length Button Width	No 3.48 mm[.137 in] 2.54 mm[.1 in]
Low Profile Process Sealed Dimensions Actuator Length Button Width Bushing Diameter	No 3.48 mm[.137 in] 2.54 mm[.1 in] 4.78 mm[.188 in]
Low Profile Process Sealed Dimensions Actuator Length Button Width Bushing Diameter Bushing Length	No 3.48 mm[.137 in] 2.54 mm[.1 in] 4.78 mm[.188 in]
Low Profile Process Sealed Dimensions Actuator Length Button Width Bushing Diameter Bushing Length Usage Conditions	No 3.48 mm[.137 in] 2.54 mm[.1 in] 4.78 mm[.188 in] 5.49 mm[.216 in]
Low Profile Process Sealed Dimensions Actuator Length Button Width Bushing Diameter Bushing Length Usage Conditions Temperature Rating	No 3.48 mm[.137 in] 2.54 mm[.1 in] 4.78 mm[.188 in] 5.49 mm[.216 in]
Low Profile Process Sealed Dimensions Actuator Length Button Width Bushing Diameter Bushing Length Usage Conditions Temperature Rating Packaging Features	3.48 mm[.137 in] 2.54 mm[.1 in] 4.78 mm[.188 in] 5.49 mm[.216 in] High
Low Profile Process Sealed Dimensions Actuator Length Button Width Bushing Diameter Bushing Length Usage Conditions Temperature Rating Packaging Features Packaging Method	3.48 mm[.137 in] 2.54 mm[.1 in] 4.78 mm[.188 in] 5.49 mm[.216 in] High

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Yet Reviewed
20 Notice Directive 2011/00/20	140010010000



EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2021 (211) Candidate List Declared Against: JUN 2016 (169) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts














Also in the Series | Alcoswitch TPB



Customers Also Bought

















Documents

Product Drawings
TPB11CGRA0=TPB PUSHBUTTON BLAC

English

Datasheets & Catalog Pages

TP Series Data Sheet

English