

## Power Cord with Locking System for Inlet Filters IL 13, IL 13 P, IL 19



- Locking system for standardized IEC C14/C20 inlet filter
- No accidental disconnection
- Rated current up to 10 A (C13 plug), up to 15 A (C13P plug), and up to 20 A (C19 plug)
- Fits any Schaffner IEC C14/C20 inlet filter
- Retrofit for any IEC C14/C20 inlet
- Various power line plugs for international usage



### Approvals



The locking system has a tensile force of typical 200N. It is recommended to use it with flange mount filters. For details refer to our Application Note "Using IEC Lock Power Cords with IEC Inlets and Filters"

Schaffner power cords with IEC lock guard against accidental disconnection of all electrical appliances with an IEC inlet. No exchange or modification of the IEC inlet or IEC inlet filter system is needed. Easy retrofit for all electronic equipments and devices.

### Technical specifications IL 13/IL 13 P

|  |   |
|--|---|
| <b>Maximum continuous operating voltage</b>      | 250 VAC, 50/60 Hz   |
| <b>Rated currents</b>                            | 10 A for C13 plug, 15 A for C13P plug   |
| <b>High potential test voltage</b>               | P→ PE 2000 VAC (1 min 50 Hz)<br>P → N 2000 VAC (1 min 50 Hz)  |
| <b>Protection category</b>                       | IP 20 according IEC 60529   |
| <b>Temperature range (operation and storage)</b> | -25°C to +70°C  |
| <b>Connector (load side)</b>                     | IEC C13 according to IEC/EN 60320-2-2 with IEC Lock UL 498, CSA C22.2 no. 42 (for cold conditions) pin temp. 70°C, up to 15 A, Protection Class I |
| <b>Connector (line side) and cables</b>          | Please refer to table on page 2 and 3   |
| <b>Flammability corresponding to</b>             | Plugs: UL 94 V-2 or better; Cable: IEC 60332-1 Cat. F2  |

### Features and benefits

- Power cord with locking system for IEC inlets
- Protection class I (IL 13, IL 13 P)
- Suitable for use with any C14 IEC inlet (IL 13, IL 13 P) and C20 IEC inlet (IL 19)
- Fits the complete Schaffner IEC inlet filter program with C14 IEC inlet and C20 IEC inlet (IL 19)
- Max. pin temperature 70°C

### Typical applications

- Data centers
- Industrial equipment
- Medical devices
- In-vitro diagnostic devices
- Broadcasting stations
- Mobile applications

### Technical specifications IL 19

|  |  |
|--|--|
| <b>Maximum continuous operating voltage</b>      | 250 VAC, 50/60 Hz  |
| <b>Rated currents</b>                            | 16 A (IEC), 20 A (UL)  |
| <b>Operating frequency</b>                       | 50 to 400 Hz   |
| <b>High potential test voltage</b>               | P→ PE 2000 VAC (1 min 50 Hz)<br>P → N 2000 VAC (1 min 50 Hz)   |
| <b>Protection category</b>                       | IP 20 according IEC 60529  |
| <b>Temperature range (operation and storage)</b> | -25°C to +70°C   |
| <b>Connector (load side)</b>                     | IEC C19 according to IEC/EN 60320-2-2 with IEC lock, UL 498, CSA C22.2 no. 42 (for cold conditions) pin temp. 70°C, up to 20 A, Protection Class I |
| <b>Connector (line side) and cables</b>          | please refer to table on page 4  |
| <b>Flammability corresponding to</b>             | Plugs: UL 94 V-2 or better; Cable: IEC 60332-1 Cat. F2   |

## Cable selection table IL 13

|                                |  |
|--------------------------------|--|
| <b>IL 13-C14-H05-3100-X*</b>   | IEC cable assembly with locking system for IEC C14 inlet, EU version                 |
| <b>IL 13-C14-SVT-3100-X*</b>   | IEC cable assembly with locking system for IEC C14 inlet, US version                 |
| <b>IL 13-CH1-H05-3100-X*</b>   | IEC cable assembly with locking system for IEC C14 inlet, CH version                 |
| <b>IL 13-EU1-H05-3100-X*</b>   | IEC cable assembly with locking system for IEC C14 inlet, EU version                 |
| <b>IL 13-JP1-HVCTF-3125-X*</b> | IEC cable assembly with locking system for IEC C14 inlet, JP version                 |
| <b>IL 13-SE-H05-3100-X*</b>    | IEC cable assembly with locking system for IEC C14 inlet, stripped ends              |
| <b>IL 13-UK1-H05-3100-X*</b>   | IEC cable assembly with locking system for IEC C14 inlet, UK version                 |
| <b>IL 13-US1-SVT-3100-X*</b>   | IEC cable assembly with locking system for IEC C14 inlet, US version                 |
| <b>IL 13-US2-SJT-3100-X*</b>   | IEC cable assembly with locking system for IEC C14 inlet, US version, hospital grade |

To compile a complete part number, please replace the X\* with the required length (please refer to table below for available length per cable type):

- X\* options = 200, 300, 400, 500 or 1000 cm; 183, 275 or 366 cm (6, 9 or 12 feet)

## Available combinations IL 13

To compile a complete part number exchange the letters (IL13-yyy-zzz-aaaa-bbb-c) with the data from the table below.

| Load side IL13 |   | Line side plug  |         | Cable type      |            | Cable core                                     |                      | Rating                      | Cable length* |     | Cable color                             |                       | Cert.                   |
|----------------|---|---|---------|-----------------|------------|--|----------------------|-----------------------------|---------------|-----|---|-----------------------|-------------------------|
| IL13           |   | yyy   |         | zzz             |            | aaaa   |                      |                             | bbb           |     | c                                       |                       |                         |
| IL13           | IEC C13<br>Female plug,<br>straight, lock | IEC C14, male, straight<br>Australian plug 3 pins<br>SEV1011, straight<br>CEE 7/VII, right angled or straight<br>Italian Plug<br>Israel Plug<br>Korean Plug<br>South African Plug<br>Stripped Ends<br>BS1363, right angled fused 5A<br>BS1363, right angled fused 10A | C14     | H05VV-F         | H05        | 3x1.00mm <sup>2</sup>                          | 3100                 | 250VAC<br>10A               | 6 feet        | 183 | Black<br>Blue<br>Orange<br>Red<br>White | -<br>B<br>O<br>R<br>W | CB<br>KC<br>KEMA<br>SAA |
|                |   |   | 200 cm  |                 |            |  |                      |                             | 200           |     |   |                       |                         |
|                |   |   | 9 feet  |                 |            |  |                      |                             | 275           |     |   |                       |                         |
|                |   |   | 300 cm  |                 |            |  |                      |                             | 300           |     |   |                       |                         |
|                |   |   | 12 feet |                 |            |  |                      |                             | 366           |     |   |                       |                         |
|                |   |   | 400 cm  |                 |            |  |                      |                             | 400           |     |   |                       |                         |
|                |   |   | 500 cm  |                 |            |  |                      |                             | 500           |     |   |                       |                         |
| 1000 cm        | 1000                                      |   |         |                 |            |  |                      |                             |               |     |   |                       |                         |
| IL13           | IEC C13<br>Female plug,<br>straight, lock | IEC C14, male, straight<br>Japanese Plug JIS C8303 insulated sleeves<br>Stripped Ends   | C14     | HVCTF           | HVCTF      | 3x1.25mm <sup>2</sup><br>3x2.00mm <sup>2</sup> | 3125<br>3200         | 125VAC<br>12A<br>15A        | 100 cm        | 100 | Black<br>Blue<br>Orange<br>Red<br>White | -<br>B<br>O<br>R<br>W | PSE                     |
|                |   |   | 200 cm  |                 |            |  |                      |                             | 200           |     |   |                       |                         |
|                |   |   | 300 cm  |                 |            |  |                      |                             | 300           |     |   |                       |                         |
|                |   |   | 400 cm  |                 |            |  |                      |                             | 400           |     |   |                       |                         |
|                |   |   | 500 cm  |                 |            |  |                      |                             | 500           |     |   |                       |                         |
| IL13           | IEC C13<br>Female plug,<br>straight, lock | IEC C14, male, straight<br>Stripped Ends<br>NEMAS-15, straight<br>NEMAS-15, straight, hospital grade  | C14     | SJT<br>SVT      | SJT<br>SVT | AWG 18<br>AWG 16<br>AWG 14                     | 3100<br>3130<br>3160 | 125VAC<br>10A<br>13A<br>15A | 6 feet        | 183 | Black<br>Blue<br>Orange<br>Red<br>White | -<br>B<br>O<br>R<br>W | UL<br>cUL               |
|                |   |   | 200 cm  |                 |            |  |                      |                             | 200           |     |   |                       |                         |
|                |   |   | 9 feet  |                 |            |  |                      |                             | 275           |     |   |                       |                         |
|                |   |   | 300 cm  |                 |            |  |                      |                             | 300           |     |   |                       |                         |
|                |   |   | 12 feet |                 |            |  |                      |                             | 366           |     |   |                       |                         |
|                |   |   | 400 cm  |                 |            |  |                      |                             | 400           |     |   |                       |                         |
|                |   |   | 500 cm  |                 |            |  |                      |                             | 500           |     |   |                       |                         |
| 1000 cm        | 1000                                      |   |         |                 |            |  |                      |                             |               |     |   |                       |                         |
| IL13           | IEC C13<br>Female plug,<br>straight, lock | IEC C14, male, straight<br>Chinese plug<br>Stripped Ends  | C14     | RVV             | RVV        | 3x1.00mm <sup>2</sup>                          | 3100                 | 250VAC<br>10A               | 200 cm        | 200 | Black<br>Blue<br>Orange<br>Red<br>White | -<br>B<br>O<br>R<br>W | CCC                     |
|                |   |   | CN1     |                 |            |  |                      |                             |               |     |   |                       |                         |
|                |   |   | SE      |                 |            |  |                      |                             |               |     |   |                       |                         |
|                |   |   | SE      |                 |            |  |                      |                             |               |     |   |                       |                         |
|                |   |   | SE      |                 |            |  |                      |                             |               |     |   |                       |                         |
| IL13           | IEC C13<br>Female plug,<br>straight, lock | IEC C14, male, straigh<br>Indian plug 3 Pin<br>Stripped Ends  | C14     | IS 694<br>1000V | IS694      | 3x1.00mm <sup>2</sup>                          | 3100                 | 250VAC<br>10A               | 200 cm        | 200 | Black<br>Blue<br>Orange<br>Red<br>White | -<br>B<br>O<br>R<br>W | CB                      |
|                |   |   | IN1     |                 |            |  |                      |                             |               |     |   |                       |                         |
|                |   |   | SE      |                 |            |  |                      |                             |               |     |   |                       |                         |
|                |   |   | SE      |                 |            |  |                      |                             |               |     |   |                       |                         |
|                |   |   | SE      |                 |            |  |                      |                             |               |     |   |                       |                         |

\*feet values are calculated to the matching length in cm

## Cable selection table IL 13 P

|                                  |   |
|----------------------------------|---|
| <b>IL 13 P-C14-H05-3100-X*</b>   | IEC cable assembly with locking system + for IEC C14 inlet, EU version    |
| <b>IL 13 P-CH1-H05-3100-X*</b>   | IEC cable assembly with locking system + for IEC C14 inlet, CH version    |
| <b>IL 13 P-EU1-H05-3100-X*</b>   | IEC cable assembly with locking system + for IEC C14 inlet, EU version    |
| <b>IL 13 P-JP1-HVCTF-3125-X*</b> | IEC cable assembly with locking system + for IEC C14 inlet, JP version    |
| <b>IL 13 P-SE-H05-3100-X*</b>    | IEC cable assembly with locking system + for IEC C14 inlet, stripped ends |
| <b>IL 13 P-UK1-H05-3100-X*</b>   | IEC cable assembly with locking system + for IEC C14 inlet, UK version    |
| <b>IL 13 P-US1-SJT-3160-X*</b>   | IEC cable assembly with locking system + for IEC C14 inlet, US version    |

To compile a complete part number, please replace the X\* with the required length (please refer to table below for available length per cable type):

- X\* options = 200, 300, 400, 500 or 1000 cm; 183, 275 or 366 cm (6, 9 or 12 feet)

## Available combinations IL 13 P

To compile a complete part number exchange the letters (IL13P-yyy-zzz-aaaa-bbb-c) with the data from the table below.

| Load side IL13P |   | Line side plug   |        | Cable type      |       | Cable core            |      | Rating        | Cable length*                         |                                  | Cable color                             |                       | Cert.                   |
|-----------------|---|--|--------|-----------------|-------|-----------------------|------|---------------|---------------------------------------|----------------------------------|---|-----------------------|-------------------------|
| IL13P           |   | yyy  |        | zzz             |       | aaaa                  |      |               | bbb                                   |                                  | c                                       |                       |                         |
| IL13P           | IEC C13 +<br>Female plug,<br>straight, lock | IEC C14, male, straight<br>Australian plug 3 pins<br>SEV1011, straight<br>CEE 7/VI, right angled or straight<br>Italian Plug<br>Israel Plug<br>Korean Plug<br>South African Plug<br>Stripped Ends<br>BS1363, right angled fused 5A<br>BS1363, right angled fused 10A | C14    | H05VV-F         | H05   | 3x1.00mm <sup>2</sup> | 3100 | 250VAC<br>10A | 6 feet                                | 183                              | Black<br>Blue<br>Orange<br>Red<br>White | -<br>B<br>O<br>R<br>W | CB<br>KC<br>KEMA<br>SAA |
|                 |   |  | 200 cm |                 |       |                       |      |               | 200                                   |                                  |   |                       |                         |
| IL13P           | IEC C13 +<br>Female plug,<br>straight, lock | IEC C14, male, straight<br>Japanese Plug JIS C8303 insulated sleeves<br>Stripped Ends  | C14    | HVCTF           | HVCTF | 3x1.25mm <sup>2</sup> | 3125 | 125VAC        | 100 cm                                | 100                              | Black<br>Blue<br>Orange<br>Red<br>White | -<br>B<br>O<br>R<br>W | PSE                     |
|                 |   |  | JP1    |                 |       | 3x2.00mm <sup>2</sup> | 3200 | 12A<br>15A    | 200 cm<br>300 cm<br>400 cm<br>500 cm  | 200<br>300<br>400<br>500         |   |                       |                         |
| IL13P           | IEC C13 +<br>Female plug,<br>straight, lock | IEC C14, male, straight<br>Stripped Ends<br>NEMA5-15, straight<br>NEMA5-15, straight, hospital grade   | C14    | SJT             | SJT   | AWG 18                | 3100 | 125VAC        | 6 feet                                | 183                              | Black<br>Blue<br>Orange<br>Red<br>White | -<br>B<br>O<br>R<br>W | UL<br>cUL               |
|                 |   |  | SE     |                 |       | AWG 16                | 3130 | 10A           | 200 cm                                | 200                              |   |                       |                         |
| IL13P           | IEC C13 +<br>Female plug,<br>straight, lock | IEC C14, male, straight<br>Chinese plug<br>Stripped Ends   | C14    | RVV             | RVV   | 3x1.00mm <sup>2</sup> | 3100 | 250VAC<br>10A | 9 feet                                | 275                              | Black<br>Blue<br>Orange<br>Red<br>White | -<br>B<br>O<br>R<br>W | CCC                     |
|                 |   |  | CN1    |                 |       | AWG 14                | 3160 | 13A<br>15A    | 300 cm<br>400 cm<br>500 cm<br>1000 cm | 300<br>366<br>400<br>500<br>1000 |   |                       |                         |
| IL13P           | IEC C13 +<br>Female plug,<br>straight, lock | IEC C14, male, straight<br>Indian plug 3 Pin<br>Stripped Ends  | C14    | IS 694<br>1000V | IS694 | 3x1.00mm <sup>2</sup> | 3100 | 250VAC<br>10A | 200 cm                                | 200                              | Black<br>Blue<br>Orange<br>Red<br>White | -<br>B<br>O<br>R<br>W | CB                      |
|                 |   |  | IN1    |                 |       | SE                    |      |               |                                       |                                  |   |                       |                         |

\*feet values are calculated to the matching length in cm

## Cable selection table IL 19

|                              |   |
|------------------------------|---|
| <b>IL 19-C20-H05-3150-X*</b> | IEC cable assembly with locking system for IEC C20 inlet, EU version    |
| <b>IL 19-C20-SJT-3160-X*</b> | IEC cable assembly with locking system for IEC C20 inlet, US version    |
| <b>IL 19-EU1-H05-3150-X*</b> | IEC cable assembly with locking system for IEC C20 inlet, EU version    |
| <b>IL 19-SE-H05-3150-X*</b>  | IEC cable assembly with locking system for IEC C20 inlet, stripped ends |
| <b>IL 19-UK1-H05-3150-X*</b> | IEC cable assembly with locking system for IEC C20 inlet, UK version    |
| <b>IL 19-US1-SJT-3160-X*</b> | IEC cable assembly with locking system for IEC C20 inlet, US version    |

To compile a complete part number, please replace the X\* with the required length (please refer to table below for available length per cable type):

- X\* options = 200, 300, 400, 500 or 1000 cm; 183, 275 or 366 cm (6, 9 or 12 feet)

## Available combinations IL 19

To compile a complete part number exchange the letters (IL19-yyy-zzz-aaa-bbb-c) with the data from the table below.

| Load side IL19                 |   | Line side plug                            | Cable type |            | Cable core |                       | Rating*      | Cable length**     |         | Cable color | Cert.                                   |                       |                   |
|--------------------------------|---|---|------------|------------|------------|-----------------------|--------------|--------------------|---------|-------------|---|-----------------------|-------------------|
| IL19                           |   | yyy                                       | zzz        |            | aaaa       |                       |              | bbb                |         | c           |   |                       |                   |
| IL19                           | IEC C19<br>Female plug,<br>straight, lock | IEC C20, male, straight                   | C20        | H05VV-F    | H05        | 3x1.50mm <sup>2</sup> | 3150         | 16A                | 6 feet  | 183         | Black<br>Blue<br>Orange<br>Red<br>White | -<br>B<br>O<br>R<br>W | CB<br>KEMA<br>SAA |
|                                |   | Australian plug 3 pins                    | AU1        |            |            |                       |              | 15A                | 200 cm  | 200         |   |                       |                   |
|                                |   | SEV1011, straight                         | CH1        |            |            |                       |              | 16A                | 9 feet  | 275         |   |                       |                   |
|                                |   | CEE 7/VII, right angled or straight       | EU1        |            |            |                       |              | 16A                | 300 cm  | 300         |   |                       |                   |
|                                |   | Italian Plug                              | IT1        |            |            |                       |              | 16A                | 12 feet | 366         |   |                       |                   |
|                                |   | South Africa plug                         | SA1        |            |            |                       |              | 16A                | 400 cm  | 400         |   |                       |                   |
|                                |   | Stripped Ends                             | SE         |            |            |                       |              | 16A                | 500 cm  | 500         |   |                       |                   |
| BS1363, right angled fused 13A | UK1                                       | 13A                                       | 1000 cm    | 1000       |            |                       |              |                    |         |             |   |                       |                   |
| IL19                           | IEC C19<br>Female plug,<br>straight, lock | IEC C20, male, straight                   | C20        | HVCTF      | HVCTF      | 3x2.00mm <sup>2</sup> | 3200         | 20A                | 100 cm  | 100         | Black<br>Blue<br>Orange<br>Red<br>White | -<br>B<br>O<br>R<br>W | PSE               |
|                                |   | Japanese Plug JIS C8303 insulated sleeves | JP1        |            |            |                       |              |                    | 200 cm  | 200         |   |                       |                   |
|                                |   | Stripped Ends                             | SE         |            |            |                       |              |                    | 300 cm  | 300         |   |                       |                   |
|                                |   |   |            |            |            |                       |              |                    | 400 cm  | 400         |   |                       |                   |
|                                |   |   |            |            |            |                       |              |                    | 500 cm  | 500         |   |                       |                   |
| IL19                           | IEC C19<br>Female plug,<br>straight, lock | IEC C20, male, straight                   | C20        | SJT<br>SVT | SJT<br>SVT | AWG14<br>AWG12        | 3160<br>3205 | 125V<br>15A<br>20A | 6 feet  | 183         | Black<br>Blue<br>Orange<br>Red<br>White | -<br>B<br>O<br>R<br>W | UL<br>cUL         |
|                                |   | Stripped Ends                             | SE         |            |            |                       |              |                    | 200 cm  | 200         |   |                       |                   |
|                                |   | NEMA5-15, straight                        | US1        |            |            |                       |              |                    | 9 feet  | 275         |   |                       |                   |
|                                |   | Nema 5-20P                                | US4        |            |            |                       |              |                    | 300 cm  | 300         |   |                       |                   |
|                                |   |   |            |            |            |                       |              |                    | 12 feet | 366         |   |                       |                   |
|                                |   |   |            |            |            |                       |              |                    | 400 cm  | 400         |   |                       |                   |
|                                |   | 500 cm                                    | 500        |            |            |                       |              |                    |         |             |   |                       |                   |
|                                |   | 1000 cm                                   | 1000       |            |            |                       |              |                    |         |             |   |                       |                   |
| IL19                           | IEC C19<br>Female plug,<br>straight, lock | Chinese plug                              | CN1        | RVVF       | RVVF       | 3x1.50mm <sup>2</sup> | 3150         | 16A                | 200 cm  | 200         | black                                   | -                     | CCC               |

\* if not seperately mentioned 250VAC is rated voltage

\*\* feet values are calculated to the matching length in cm



## Headquarters, global innovation and development

### Switzerland

#### Schaffner Group

Industrie Nord  
Nordstrasse 11e  
4542 Luterbach  
T +41 32 681 66 26  
[info@schaffner.com](mailto:info@schaffner.com)



## Sales and application centers

### China

#### Schaffner EMC Ltd. Shanghai

T20-3 C, No 565 Chuangye Road,  
Pudong district  
201201 Shanghai  
T +86 21 3813 9500  
[cschina@schaffner.com](mailto:cschina@schaffner.com)  
[www.schaffner.com.cn](http://www.schaffner.com.cn)

### Finland

#### Schaffner Oy

Sauvonrinne 19 H  
08500 Lohja  
T +358 10 567 2855  
[finlandsales@schaffner.com](mailto:finlandsales@schaffner.com)

### France

#### Schaffner EMC S.A.S.

16-20 Rue Louis Rameau  
95875 Bezons  
T +33 1 34 34 30 60  
F +33 1 39 47 02 28  
[francesales@schaffner.com](mailto:francesales@schaffner.com)

### Germany

#### Schaffner Deutschland GmbH

Schoemperlenstrasse 12B  
76185 Karlsruhe  
T +49 721 56910  
F +49 721 569110  
[germanysales@schaffner.com](mailto:germanysales@schaffner.com)

### India

#### Schaffner India Pvt. Ltd

REGUS WORLD TRADE CENTRE  
WTC, 22nd Floor Unit No 2238, Brigade  
Gateway Campus, 26/1, Dr. Rajkumar Road  
Malleshwaram (W)  
560055 Bangalore  
T +91 80 67935355  
[indiasales@schaffner.com](mailto:indiasales@schaffner.com)

### Italy

#### Schaffner EMC S.r.l.

Via Ticino, 30  
20900 Monza (MB)  
T +39 039 21 41 070  
[italysales@schaffner.com](mailto:italysales@schaffner.com)

### Japan

#### Schaffner EMC K.K.

Taiju-Seimei Sangenjaya Bldg.  
1-32-12, Kamiyama, Setagaya-ku  
154-0011 Tokyo  
T +81 3 5712 3650  
F +81 3 5712 3651  
[japansales@schaffner.com](mailto:japansales@schaffner.com)  
[www.schaffner.jp](http://www.schaffner.jp)

### Singapore

#### Schaffner EMC Pte Ltd.

#05-09, Kg Ubi Ind. Estate  
408705 Singapore  
T +65 6377 3283  
F +65 6377 3281  
[singaporesales@schaffner.com](mailto:singaporesales@schaffner.com)

### Spain

#### Schaffner EMC España

Calle Caléndula 93, Miniparc III, Edificio E  
El Soto de Moraleja, Alcobendas  
28109 Madrid  
T +34 917 912 900  
F +34 917 912 901  
[spainsales@schaffner.com](mailto:spainsales@schaffner.com)

### Sweden

#### Schaffner EMC AB

Östermalmstorg 1  
114 42 Stockholm  
T +46 8 5050 2425  
[swedensales@schaffner.com](mailto:swedensales@schaffner.com)  
[www.schaffner.com](http://www.schaffner.com)

### Switzerland

#### Schaffner EMV AG

Industrie Nord  
Nordstrasse 11e  
4542 Luterbach  
T +41 32 681 66 88  
T +41 32 681 66 26  
[switzerlandsales@schaffner.com](mailto:switzerlandsales@schaffner.com)

### Taiwan R.O.C.

#### Schaffner EMV Ltd.

20 Floor-2, No 97, Section 1, XinTai 5th Road  
22175 XiZhi District New Taipei City 22175  
T +886 2 2697 5500  
F +886 2 2697 5533  
[taiwansales@schaffner.com](mailto:taiwansales@schaffner.com)  
[www.schaffner.com.tw](http://www.schaffner.com.tw)

### Thailand

#### Schaffner EMC Co. Ltd.

Northern Region Industrial Estate  
67 Moo 4 Tambon Ban Klang  
Amphur Muangng P.O. Box 14  
51000 Lamphun  
T +66 53 58 11 04  
F +66 53 58 10 19  
[thailandsales@schaffner.com](mailto:thailandsales@schaffner.com)

### United Kingdom

#### Schaffner Ltd.

1, Oakmede Place  
Binfield  
RG42 4JF Berkshire  
T +44 118 9770070  
F +44 118 9792969  
[uksales@schaffner.com](mailto:uksales@schaffner.com)

### USA

#### Schaffner EMC Inc.

52 Mayfield Avenue  
Edison, New Jersey  
T +1 732 225 9533  
F +1 732 225 4789  
[usasales@schaffner.com](mailto:usasales@schaffner.com)  
[www.schaffnerusa.com](http://www.schaffnerusa.com)

#### Schaffner North America

6722 Thirlane Road  
24019 Roanoke, Virginia  
T +1 276 228 7943  
F +1 276 228 7953

#### Schaffner North America

823 Fairview Road  
24382 Wytheville, Virginia  
T +1 276 228 7943  
F +1 276 228 7258

To find your local partner within Schaffner's global network: [www.schaffner.com](http://www.schaffner.com)

© 2020 Schaffner Group

The content of this document has been carefully checked and understood. However, neither Schaffner nor its subsidiaries assume any liability whatsoever for any errors or inaccuracies of this document and the consequences thereof. Published specifications are subject to change without notice. Product suitability for any area of application must ultimately be determined by the customer. In all cases, products must never be operated outside their published specifications. Schaffner does not guarantee the availability of all published products. This disclaimer shall be governed by substantive Swiss law and resulting disputes shall be settled by the courts at the place of business of Schaffner Holding AG. Latest publications and a complete disclaimer can be downloaded from the Schaffner website. All trademarks recognized.