

1417788

https://www.phoenixcontact.com/pc/products/1417788

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Fixing sleeve for M12 housing screw connection with tolerance-compensating function, for THR solderable M12 socket contact inserts.

### Commercial Data

| Item number                          | 1417788       |
|--------------------------------------|---------------|
| Packing unit                         | 10 pc         |
| Minimum order quantity               | 10 pc         |
| Product Key                          | ABQCCB        |
| GTIN                                 | 4055626134468 |
| Weight per Piece (including packing) | 2.1 g         |
| Weight per Piece (excluding packing) | 2.01 g        |
| Customs tariff number                | 39269097      |
| Country of origin                    | DE            |



1417788

https://www.phoenixcontact.com/pc/products/1417788

### **Technical Data**

#### Notes

| Notes on operation | The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must |
|--------------------|--|
|                    | also be taken into consideration.  |

### Product properties

| Product type | Panel mounting base |
|--------------|---------------------|
|              |                     |

### Material specifications

| Color                                  | violet (Fixing sleeve)               |
|--|--------------------------------------|
| Material                               | PA 6.6 (Fixing sleeve)               |
| Flammability rating according to UL 94 | V0                                   |
| Sealing material                       | FKM (O-ring (pin connector pattern)) |

### Environmental and real-life conditions

#### Ambient conditions

| Degree of protection (when plugged in) | IP67 (correctly plugged in and locked)      |
|--|---|
| Degree of protection                   | IP67 (correctly plugged in and locked)      |
| Degree of protection                   | IP67, when in locked state                  |
| Ambient temperature (operation)        | -25 °C 85 °C (Plug / socket)                |
|  | -40 °C 85 °C (without mechanical actuation) |

### Standards and regulations

#### M12

| Standards/specifications IEC 61076-2-101 |
|--|
|--|

### Mounting

| Mounting type         | Rear mounting 2-section, lockable |
|-----------------------|-----------------------------------|
| Assembly instructions | 2-section, lockable               |





1417788

https://www.phoenixcontact.com/pc/products/1417788

## Drawings

### Dimensional drawing







1417788

https://www.phoenixcontact.com/pc/products/1417788

### Approvals



EAC

Approval ID: B.01687



1417788

https://www.phoenixcontact.com/pc/products/1417788

### Classifications

### **ECLASS**

|        | ECLASS-9.0    | 27440102 |
|--------|---------------|----------|
|        | ECLASS-10.0.1 | 27440102 |
|        | ECLASS-11.0   | 27440102 |
| ETIM   |               |          |
|        | ETIM 8.0      | EC002635 |
| UNSPSC |               |          |
|        | UNSPSC 21.0   | 39121400 |



1417788

https://www.phoenixcontact.com/pc/products/1417788

### **Environmental Product Compliance**

| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|------------|---|
|            | No hazardous substances above threshold values          |

Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstraße 8 D-32825 Blomberg +49 (0) 5235-3 00 info@phoenixcontact.com