

High Leverage Concreters' Nippers

high lever transmission

- ▶ 25 % less effort required compared to conventional concreters' nippers of the same size
- ▶ Extra-slim form for tying deep mounted steel rods
- > To lace concrete reinforcing steel with binding wire from a roll
- > Wire is twisted and cut in a single pass
- > High-leverage joint, minimising strain, even when thick binding wires are used
- > The high damping of the cutting stroke on cutting through the binding wire reduces the strain on tendons and muscles
- > Cutting edges additionally hardened; cutting edge hardness approx. 61 HRC
- > High-grade special tool steel, forged, multi stage oil-hardened
- > DIN ISO 9242



99 10 250



99 11 250



99 14 250



Article No.	EAN 4003773-	↔ mm		Pliers	Head	Handles	Cutting capacities		Head width Ø mm	Δ g
							● Ø mm	● Ø mm		
99 10 250	071396	250	➤	black atramentized	polished		3.3	1.8	25	350
99 10 300	022398	300	➤	black atramentized	polished		3.8	2.0	25	501
99 11 250	071402	250	➤	black atramentized	polished	plastic coated	3.3	1.8	25	350
99 11 300	042365	300	➤	black atramentized	polished	plastic coated	3.8	2.0	25	537
99 14 250	071419	250	➤	bright zinc plated			3.3	1.8	25	350
99 14 300	028116	300	➤	bright zinc plated			3.8	2.0	25	505