



## Main

Range	TeSys
Product name	TeSys GS
Device short name	GS2MU
Product or component type	Switch-disconnector-fuse
Device application	Protection
Poles description	3P
Protected poles description	3t
Contacts type and composition	3 NO
[I <sub>th</sub> ] conventional free air thermal current	200 A (at 40 °C)
[I <sub>e</sub> ] rated operational current	200 A
Fuse type	UL
Fuse size	J
Network type	DC AC
Network frequency	50/60 Hz

## Complementary

Type of operating handle	External frontal
Mounting support	Plate
[U <sub>i</sub> ] rated insulation voltage	750 V
[U <sub>imp</sub> ] rated impulse withstand voltage	8 kV
Rated operational power in W	100 kW at 400 V 140 kW at 500 V 185 kW at 690 V
Breaking capacity	1600 A at 400 V
Short-circuit withstand	32 kA
Mechanical durability	10000 cycles
Electrical durability	6000 cycles
Connections - terminals	Power circuit: lugs-ring terminals 16...152 mm <sup>2</sup>
[I <sub>cm</sub> ] rated short-circuit making capacity	2 kA at 400 V
Tightening torque	Power circuit: 8.5 N.m

## Environment

Standards	UL98 CSA C22.2 No 4
IP degree of protection	IP20 conforming to IEC 60529 (with terminal cover)
Ambient air temperature for operation	-20...70 °C
Ambient air temperature for storage	-40...80 °C
Fire resistance	960 °C body
Height	195 mm
Width	196.2 mm
Depth	130 mm

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.500 cm
Package 1 Width	24.500 cm
Package 1 Length	32.000 cm
Package 1 Weight	3.530 kg
Unit Type of Package 2	S04
Number of Units in Package 2	3
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	11.270 kg
Unit Type of Package 3	P06
Number of Units in Package 3	12
Package 3 Height	75.000 cm
Package 3 Width	60.000 cm
Package 3 Length	80.000 cm
Package 3 Weight	55.336 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>

## Contractual warranty

Warranty	18 Monate
----------	-----------