



Main

Range of product	Acti9
Product name	Acti9 STD
Product or component type	Remote control dimmer
Device short name	STD
Function available	Staircase function Scene function Automatic load type detection Configurable dimming speed

Complementary

Device application	Building
Load type	Halogen lamp: ≤ 400 W Incandescent lamp: ≤ 400 W Fluocompact lamp, dimmable: ≤ 80 W LED lamp, dimmable: ≤ 60 W Low voltage halogen lamp with electronic transformer: ≤ 300 W Low voltage halogen lamp with ferromagnetic transformer: ≤ 400 W
Control type	Local control: push-button Remote control: push-button
Power consumption in VA	0.8 VA
Thermal losses	3 W
[Ue] rated operational voltage	230 V AC - 15...10 % at 50 Hz
Input voltage	8...230 V AC/DC
Protection type	Electronic overload protection Electronic over temperature protection
Mounting support	DIN rail
9 mm pitches	2
Connected auxiliaries	Maximum 10 auxiliary push-buttons without light indication, distance : < 100 m
Switch application	Central off/on
Alarm function	Snooze Wake-up
Dimmer type	Dimmer with memory
Height	85 mm
Width	18 mm
Depth	60 mm
Net weight	70 g







Environment

IP degree of protection	IP20
Directives	2004/108/EC - electromagnetic compatibility 2006/95/EC - low voltage directive
Ambient air temperature for operation	-30...50 °C
Ambient air temperature for storage	-20...70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.3 cm
Package 1 Width	10.5 cm
Package 1 Length	3.3 cm
Package 1 Weight	126.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	86
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	11.372 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information

Contractual warranty

Warranty	18 Monate
----------	-----------