Series Click-Torque

Adjustable torque wrenches

Click-Torque X 1 torque wrench for insert tools



Application: For right and left-handed use

Precision: \pm 4% of set value, as per DIN EN ISO 6789-1: 2017-07

Design: For 9x12 mm interchangeable insert tools; easy setting and saving of the desired torque value, with audible and tactile locking when the scale

values are reached (fine scale only in Newton meters), audible and tactile release mechanism when the set torque value is reached

Handle: Ergonomic 2-component handle

)														
				 - - - - - - - - - - - - - - - - 				-	Ĭ.				-	 	•
			Nm	Nm	lbf. ft.	mm	mm	mm	mm	mm					
05 075651 0	01	9x12	2,5-25	0,10	4-18	283	121	42	24	20	11 % "	4 49/64"	1 21/32"	¹⁵ / ₁₆ "	25/32

Click-Torque X 2 torque wrench for insert tools



Application: For right and left-handed use

Precision: \pm 3% of set value, as per DIN EN ISO 6789-1: 2017-07

Design: For 9x12 mm interchangeable insert tools; easy setting and saving of the desired torque value, with audible and tactile locking when the scale

values are reached (fine scale only in Newton meters), audible and tactile release mechanism when the set torque value is reached

Handle: Ergonomic 2-component handle

-														
							-	,			-	-	Ĭ Ţ	•
		Nm	Nm	lbf. ft.	mm	mm	mm	mm	mm					
05 075652 001	9x12	10-50	0,25	8-36	338	140	47	29	20	13 ⁵ / ₁₆ "	5 ³³ / ₆₄ "	1 27/32"	1 9/ "	25/32