



Pan-Ty® PLT2H-L0 Cable Tie, Black, UV PA6.6, 8.1"L, 120lb, PK50

PLT2H-L0

Panduit PLT2H-L0 Locking Cable Ties are designed to satisfy the needs of weather resistant applications, while delivering consistent performance and reliability. Featuring a curved tip to allow for easy pick up from flat surfaces and faster initial threading. Light-heavy cross section, 8.1" (206mm) length. Made of Weather Resistant Nylon 6.6 with high resistance to ultraviolet light, are black in color and come in packages of 50.

Specifications

Product Type	Premium Cable Tie
Color	Black
Environment	Indoor/Outdoor
Material	Weather Resistant Nylon 6.6
Resistance Properties	UV Resistant
Overall Length (In.)	8.1
Overall Length (mm)	206
Body Width (In.)	0.3
Body Width (mm)	7.6
Body Thickness (In.)	0.075
Body Thickness (mm)	1.9
Maximum Bundle Diameter (In.)	2
Maximum Bundle Diameter (mm)	51
Minimum Bundle Diameter (In.)	0.188
Minimum Bundle Diameter (mm)	4.8
Minimum Loop Tensile Strength (N)	534
Minimum Loop Tensile Strength (lb)	120
Maximum Operating Temperature (°C)	85
Maximum Operating Temperature (°F)	185
Minimum Operating Temperature (°C)	-60
Minimum Operating Temperature (°F)	-76
Minimum Installation Temperature (°C)	-20
Minimum Installation Temperature (°F)	-4
Standards Met	UL 62275 Compliant (Type 2, 21), UL Recognized (File #E56854), CSA Certified, RoHS Compliant
For Use With	GTH-E, GS4H-E, GS4EH-E, PTH, STH2, ST3EH

Specifications (continued)

Part Features	One piece construction provides consistent, reliable performance. Low thread force.
---------------	--

Packaging Detail

UPC	07498354156
Std. Pkg. Qty.	50
Std. Pkg. Volume (cf)	0.0321
Std. Ctn. Qty.	500
Std. Ctn. Volume (cf)	0.3207