Cable Shears



95 16 165 ^①

tool chrome plated, handles insulated with multi-component grips, VDE-tested IEC $60900 \mathrm{DIN} \; \mathrm{EN} \; 60900$



95 26 165

tool chrome plated, handles insulated with multi-component grips, VDE-tested Style 2:internal opening spring, protected and captive IEC 60900DIN EN 60900

£ 1000 V (1000 V (100

- for cutting copper and aluminium single conductors as well as multiple stranded cables
- not suitable for steel wire and hard drawn copper conductors
- precision ground, hardened blades
- clean and smooth cut without crushing and deformation
- easy cutting with one-hand operation
- guard prevents operators' fingers being pinched
- adjustable bolted joint, self-retaining screw
- High-grade special tool steel, forged, oil-hardened

	Article No.	EAN 4003773	Style		₩ Ø mm		mm ²		AWG		∆ d g
	<u>95 16 165</u>	039648	1	15,00		50,00		1/0	165	262	
	<u>95 26 165</u>	069980	2	15,00		50,00		1/0	165	275	
technical change and errors excepted											



Cut performed with a Diagonal Cutter: high effort required, inaccurate cut, considerable deforming and crushing of the cable



Cut performed with a Cable Shear: easy, clean cut without any deformation of the cable

