

#### MTA | MTA 156


TE Internal #: 640384-6

MTA 156, Rectangular Power Connectors, Header, Plug, Wire-to-Board, 6 Position, 3.96mm [.156in] Centerline, Printed Circuit Board, UL 94V-0


View on TE.com >



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors











Rectangular Power Connector Type: Header

Connector & Housing Type: Plug
Connector System: Wire-to-Board

Number of Positions: 6

Centerline (Pitch): 3.96 mm [.156 in]

#### **Features**

### **Product Type Features**

| Header Type                       | Unshrouded            |
|-----------------------------------|-----------------------|
| Rectangular Power Connector Type  | Header                |
| Connector & Housing Type          | Plug                  |
| Connector System                  | Wire-to-Board         |
| Sealable                          | No                    |
| Connector & Contact Terminates To | Printed Circuit Board |
| Configuration Features            |                       |
| Number of Positions               | 6                     |
| PCB Mount Orientation             | Vertical              |
| Number of Power Positions         | 6                     |
| Number of Rows                    | 1                     |
| Electrical Characteristics        |                       |

600 VAC

Operating Voltage



| Contact Layout                                 | Inline                     |
|------------------------------------------------|----------------------------|
| Contact Underplating Material                  | Nickel                     |
| Contact Base Material                          | Copper Alloy               |
| Contact Current Rating (Max)                   | 7 A                        |
| Contact Retention Within Housing               | Without                    |
| Contact Type                                   | Pin                        |
| PCB Contact Termination Area Plating Material  | Tin                        |
| Contact Mating Area Plating Material           | Tin                        |
| Contact Mating Area Plating Material Thickness | 2.54 μm[100 μin]           |
|                                                | 15 μin                     |
| Termination Features                           |                            |
| Termination Post & Tail Length                 | 3.56 mm[.14 in]            |
| Termination Method to Printed Circuit Board    | Through Hole - Solder      |
| Mechanical Attachment                          |                            |
| Strain Relief                                  | Without                    |
| Mating Alignment                               | Without                    |
| PCB Mount Alignment                            | Without                    |
| Panel Mount Feature                            | Without                    |
| PCB Mount Retention                            | Without                    |
| Connector Mounting Type                        | Board Mount                |
| Mating Retention                               | Without                    |
| Housing Features                               |                            |
| Centerline (Pitch)                             | 3.96 mm[.156 in]           |
| Housing Color                                  | Natural                    |
| Housing Material                               | Polyester - GF             |
| Dimensions                                     |                            |
| PCB Thickness (Recommended)                    | 1.6 mm[.063 in]            |
| Mating Post Length                             | 10.16 mm[.4 in]            |
| Length                                         | 23.77 mm[.936 in]          |
| Usage Conditions                               |                            |
| Operating Temperature Range                    | -55 – 105 °C[-67 – 221 °F] |
| Operation/Application                          |                            |



| Circuit Application    | Power                                                        |
|------------------------|--------------------------------------------------------------|
| Industry Standards     |                                                              |
| CSA Rating             | Certified                                                    |
| UL Flammability Rating | UL 94V-0                                                     |
| Glow Wire Rating       | Standard Part - Not Glow Wire                                |
| Agency/Standard Number | E28476                                                       |
| Agency/Standard        | CSA, UL                                                      |
| UL Rating              | Recognized                                                   |
| CSA File Number        | LR7189                                                       |
| Packaging Features     |                                                              |
| Packaging Method       | Package                                                      |
| Packaging Quantity     | 1000                                                         |
| Other                  |                                                              |
| For Use With           | MTA .156 Connector Assembly or SL .156<br>Connector Assembly |

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU                  | Compliant                                                                                                               |
|-----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| EU ELV Directive 2000/53/EC                   | Compliant                                                                                                               |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold                                                                                 |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JAN 2020 (205) Candidate List Declared Against: JUL 2019 (201) Does not contain REACH SVHC |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JAN 2020<br>(205)<br>Candidate List Declared Against: JUL 2019<br>(201)                    |
| Halogen Content                               | Not Low Halogen - contains Br or Cl > 900 ppm.                                                                          |
| Solder Process Capability                     | Wave solder capable to 265°C                                                                                            |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as



EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked.Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

## Compatible Parts













06P MTA156 CONN ASSY 24AWG

WHT



























06P MTA156 CONN ASSY 18AWG

ORA





Also in the Series MTA 156







PCB Connector Keying(2



PCB Connector Mounting(1)



Power Contacts(3)



Rectangular Power Connectors(749)



Standard Rectangular Connectors (1310)



Wire-to-Board Connector Contacts(12)



Wire-to-Board Headers & Receptacles (729)

# Customers Also Bought





TE Model / Part #640384-2 02P MTA156 HDR ASSY STR RND SN



TE Model / Part #103906-7 08 MTE HDR SRRA LATCH .100CL



TE Model / Part #5-146308-3 06 MODII HDR DRRA B/A .100
















#### **Documents**

#### **Product Drawings**

06P MTA156 HDR ASSY STR RND SN

English

#### **CAD Files**

**Customer View Model** 

ENG\_CVM\_CVM\_640384-6\_AC.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_640384-6\_AC.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_640384-6\_AC.2d\_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

#### Datasheets & Catalog Pages

MTA, CST-100 II, SL-156 and AMP Economy Power (EP) Connectors

English

#### **Product Environmental Compliance**

**Product Compliance** 

English

**Product Compliance** 

English

MTA 156, Rectangular Power Connectors, Header, Plug, Wire-to-Board, 6 Position, 3.96mm [.156in] Centerline, Printed Circuit Board, UL 94V-0



Agency Approvals

Agency Approval Document

English

Agency Approval Document

English